3M™ Fire Barrier Blocks, Plugs and Planks

3M™ Fire Barrier Blocks and Planks are pre-formed foam units designed for easy installation to effectively seal medium to large openings in wall and floor through-penetrations against smoke, toxic gas and flame. Plugs are designed for up to 5 inch diameter openings.

- No cure time means faster completion
- Paintable with primer
- Installation requires no special tools
- Can be repaired and reused as needed, saving time and labor
- Firestop tested in accordance with ASTM E 814/UL 1479
- Can be sealed with 3M™ Fire Barrier Rated Foam FIP 1-Step and other 3M™ Fire Barrier Sealants (sold separately)







WALL OPENING
UP TO 2 HOUR Fire Protection

3M™ Fire Barrier Moldable Putty Stix MP+

A one-part, ready-to-use, re-enterable, intumescent putty that can be easily formed to firestop through penetrations and blank openings in fire-rated assemblies. Often used to fill voids in large openings and/or complex firestop systems.

- Up to 4-hours fire ratings per ASTM E 814 (UL 1479)
- Provides draft and cold smoke seal
- Helps reduce noise transfer (STC-Rating of 56 when tested in STC 56-rated wall assembly)
- Noncorrosive to metal and compatible with synthetic cable jackets
- Will not dry out or crumble, re-enterable



CLASSIFIED UL — FILL, VOID OR CAVITY MATERIAL FOR USE IN THROUGH-PENETRATION FIRESTOP SYSTEMS SEE UL FIRE RESISTANCE DIRECTORY 9OGD

ULC LISTED — FILL, VOID OR CAVITY MATERIALS 9OGD

FM APPROVED — SUBJECT TO THE CONDITIONS OF APPROVAL AS A WALL & FLOOR PENETRATION FIRESTOP WHEN INSTALLED AS DESCRIBED IN THE CURRENT EDITION OF THE FMRC APPROVAL GUIDE

Intertek — FIRESTOP SYSTEMS SEE INTERTEK DIRECTORY

FIRE BARRIER: UP TO 4 HOUR Fire Protection
SMOKE SEAL: L RATED Meets Optional L Requirements
WALL OPENING: UP TO 2 HOUR Fire Protection
SOUND BARRIER: STC 52 In STC 53-Rated Wall Assembly

3M™ Fire Barrier Moldable Putty Pads MPP+

A one-part firestop material used in various fire-rated assemblies, such as electrical box protection and wall openings. Ready to use in convenient, thick pads.

- Provides draft and cold smoke seal, helps reduce noise transfer
- Up to 4-hour fire ratings per ASTM E 814 (UL 1479)
- Excellent adhesion to a wide range of construction materials



FIRE BARRIER: UP TO 4 HOUR Fire Protection
SMOKE SEAL: L RATED Meets Optional L Requirements
WALL OPENING: UP TO 2 HOUR Fire Protection
SOUND BARRIER: STC 52 In STC 53-Rated Wall Assembly

Intertek — FIRESTOP SYSTEMS SEE INTERTEK DIRECTORY

CLASSIFIED UL — FILL, VOID OR CAVITY MATERIAL FOR USE IN THROUGH-PENETRATION FIRESTOP SYSTEMS SEE UL FIRE RESISTANCE DIRECTORY 9OGD

ULC LISTED — FILL, VOID OR CAVITY MATERIALS 9OGD

FM APPROVED — SUBJECT TO THE CONDITIONS OF APPROVAL AS A WALL & FLOOR PENETRATION FIRESTOP WHEN INSTALLED AS DESCRIBED IN THE CURRENT EDITION OF THE FMRC APPROVAL GUIDE