

[Main Page](#)[Company Profile](#)[Employment](#)[What's New](#)[Contact Us](#)**ALLIED MOULDED
PRODUCTS, Inc****Residential Products**

>> Residential Home : Choose a Category Below

[Contractor Testimonial -
Residential Outlet Boxes](#)[Inspector Information](#)[Fiberglassbox™ Switch and
Outlet Boxes](#)[Fiberglassbox™ Old Work
Outlet Boxes](#)[SLIDERBOX® Adjustable
Outlet Boxes](#)[Flexbox® Switch and Outlet
Boxes](#)[Flexbox® Old Work Outlet
Boxes](#)[Floor Box Assemblies](#)[Red Fire Alarm Boxes](#)[Paddle Fan & Fixture Support
Boxes](#)[Structured Cable/Low
Voltage Products](#)[Vapor Seal/Air-Sealed Type
Boxes](#)[Range/Dryer Receptacle Box](#)[Lampholders](#)[Compact Fluorescent
Fixtures](#)[Speed "K" Klamps™](#)[Request a Catalog](#)[Your New Product Ideas](#)[Residential Home Brochure](#)[Material Safety Data Sheets](#)[Made In USA](#)[Rep Login](#)**FB-3N**[Request a Catalog](#)[Find a Sales Rep](#)[Find a Stocking Distributor](#)[Email Link to This](#)**Round floor box, nickel
plated cover, duplex
device**

Wiring Cap. (Cu. In.): 24.5

Depth (In.): 3.0

Width (In.): 3.9 dia.

Height (In.):

Cut-In Size: 4 in. dia.

Standard Quantity: 6

Standard Weight (Lbs.): 9

UPC: 8533994130

Material of Construction:*Box:* thermoplastic*Cover:* brushed nickel plated*Cover Gasket:* closed-cell rubber*Dust Plate:* galvanized steel*Receptacle:* Nonmetallic, Tamper

Resistant; 15 amp 125 volt with

ground

Test Spec: UL® Listed per UL® 514 C

Cover seal meets UL 514C scrub-
water exclusion testFire Rating Classification: 2-HR Floor
AssembliesDesigned in the U.S.A.
Made in China[Main Page](#) | [Company Profile](#) | [Employment](#) | [Products](#) | [Sitemap](#) | [Contact Us](#) | [Electrical Box](#) | [Fan Box](#) | [Outlet Box](#)

© Copyright Allied Moulded Products, Inc. 222 N. Union St., Bryan, OH 43506. Phone: 419-636-4217

THE EXPERTS IN ELECTRICAL BOXES