



>> Residential Home : Choose a Category Below

[Contractor Testimonial - Residential Outlet Boxes](#)[Inspector Information](#)[Fiberglassbox™ Switch and Outlet Boxes](#)[Fiberglassbox™ Old Work Outlet Boxes](#)[SLIDERBOX® Adjustable Outlet Boxes](#)[Flexbox® Switch and Outlet Boxes](#)[Flexbox® Old Work Outlet Boxes](#)[Floor Box Assemblies](#)[Red Fire Alarm Boxes](#)[Paddle Fan & Fixture Support Boxes](#)[Structured Cable/Low Voltage Products](#)[Vapor Seal/Air-Sealed Type Boxes](#)[Range/Dryer Receptacle Box](#)[Lampholders](#)[Compact Fluorescent Fixtures](#)[Speed "K" Klamps™](#)[Request a Catalog](#)[Your New Product Ideas](#)[Residential Home Brochure](#)[Material Safety Data Sheets](#)[Made In USA](#)[Rep Login](#)**FB-2N**[Request a Catalog](#)[Find a Sales Rep](#)[Find a Stocking Distributor](#)[Email Link to This](#)**Rectangular floor box, nickel plated cover, duplex device**

Wiring Cap. (Cu. In.): 24.5

Depth (In.): 3.5

Width (In.): 2.498

Height (In.): 4.312

Cut-In Size: 2.625 in. X 4.437 in.

Standard Quantity: 6

Standard Weight (Lbs.): 8

UPC: 8533994129

Material of Construction:*Box:* thermoplastic*Cover:* brushed nickel plated*Cover Gasket:* closed-cell rubber*Dust Plate:* galvanized steel*Receptacle:* Nonmetallic, Tamper

Resistant; 15 amp 125 volt with ground

Test Spec: UL® Listed per UL® 514 C

Cover seal meets UL 514C scrub-water exclusion test

Fire Rating Classification: 2-HR Floor Assemblies

Designed in the U.S.A.
Made in China