

fiberglassBOX™ 4" Dia. Round Outlet

Wall or Ceiling Fixture Support Boxes



NOTE: All 4" round outlet boxes have combination fixture mounting patterns (at widths of 2.75" and 3.5") with machine tapped holes to accept #8-32 mounting hardware.

Bottom Mount	Cu. In. Volume	Catalog Number	Component Description	Exterior Dimensions		Fixture Rating	UPC# 85339	Std. Pkg. Qty.	Std. Wt. (lb.)
				D	W				
	15.0	9364	Bottom mount, Speed Klamps™ - bulk packed	1-11/16	4	50 lb.	15080	50	25
	15.0	9364-K	Bottom mount, Speed Klamps™ - factory installed	1-11/16	4	50 lb.	10622	50	25
	22.5	9350	OBSOLETE: Replaced by 9350-K						
	22.5	9350-K	Bottom mount, Speed Klamps™ - factory installed	2-7/16	4	50 lb.	10418	50	21

Nail-On	Cu. In. Volume	Catalog Number	Component Description	Exterior Dimensions		Fixture Rating	UPC# 85339	Std. Pkg. Qty.	Std. Wt. (lb.)
				D	W				
	15.0	9365-N	Fetter ring nails, Speed Klamps™ - bulk packed	1-11/16	4	50 lb.	10630	50	21
	15.0	9365-NK	Fetter ring nails, Speed Klamps™ - factory installed	1-11/16	4	50 lb.	75391	50	22
	22.5	9351-N	Fetter ring nails, Speed Klamps™ - bulk packed	2-7/16	4	50 lb.	10475	48	25
	22.5	9351-NC2	Fetter ring nails, 2 wire clamps - factory installed	2-7/16	4	50 lb.	65190	48	26
	22.5	9351-NK	Fetter ring nails, Speed Klamps™ - factory installed	2-7/16	4	50 lb.	10476	48	25
	22.5	9351-NKRED	Fetter ring nails, Speed Klamps™ - factory installed *Molded in red for fire circuits	2-7/16	4	50 lb.	96502	25	13
	22.5	9351-NG	OBSOLETE: Replaced by 9351-NGK						
	22.5	9351-NGC2	Fetter ring nails, ground strap, 2 wire clamps - factory installed	2-7/16	4	50 lb.	65220	48	26
	22.5	9351-NGK	Fetter ring nails, ground strap, Speed Klamps™ - factory installed	2-7/16	4	50 lb.	65212	48	26
	★ 22.5	9352-NK	Fetter ring nails, Speed Klamps™ - factory installed	2-7/16	4	50 lb.	98477	48	27
	★ 22.5	9352-NGK	Fetter ring nails, ground strap, Speed Klamps™ - factory installed	2-7/16	4	50 lb.	98488	48	27

★ New Product!



9351-SSK

Steel Stud Screws	Cu. In. Volume	Catalog Number	Component Description	Exterior Dimensions		Fixture Rating	UPC# 85339	Std. Pkg. Qty.	Std. Wt. (lb.)
				D	W				
	22.5	9351-SS	OBSOLETE: Replaced by 9351-SSK						
	22.5	9351-SSK	Steel stud screws for use with non-load-bearing studs 22 gauge or lighter, Speed Klamps™ - factory installed	2-7/16	4	50 lb.	65992	48	24

All dimensions are in inches unless otherwise noted.
See page 7 for Attachment Coding suffix descriptions.

Old Work/Manufactured Housing Boxes

Outlet Box
UL File No. E30594