



**ALLIED
MOULDED
PRODUCTS, Inc.**

222 N Union Street • Bryan, OH 43506
Ph: (800) 722-2679 • Fx: (800) 237-7269

Email: sales@alliedmoulded.com
www.alliedmoulded.com

SB-3



VIDEO

Product Description

Three gang adjustable electrical box for use with nonmetallic sheathed cable

Brand: SLIDERBOX®
Catalog #: SB-3

Height: 3-3/4 in.
Width: 5-13/16 in.
Depth: 3-9/16 in.
Volume: 61 cu. in.

Type of Installation: Old or New Work
Wall Box
Number of Gangs: 3

Carton Quantity: 6
Carton Weight: 3 lb.

UPC: 085339945024
UNSPSC: 39121308
Patents:
U.S. Patent No. 7,855,338

U.S. Patent No. 6,365,831 B1
Country of Origin: United States of America

FEATURES

Molded-in splined device holes, adjustable slider plate for additional wall substrate thickness, slot provision for low voltage divider, rectangular exterior for easy cut-in, leveling ribs, offset gauge marks

APPLICATION

New and old work residential construction 2 HR fire resistive walls and ceilings

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Polycarbonate

MOUNTING

Internal screws with adjustable slider plate for substrates 1/2" to 1 3/8"

ADDITIONAL MATERIALS

Carbon steel fasteners