



**ALLIED
MOULDED
PRODUCTS, Inc.**

222 N Union Street • Bryan, OH 43506
Ph: (800) 722-2679 • Fx: (800) 237-7269

Email: sales@alliedmoulded.com
www.alliedmoulded.com

RD-42V



VIDEO

Product Description

Range/dryer electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™ - Vapor Seal
Catalog #: RD-42V

Height: 3-3/4 in.
Width: 4 in.
Depth: 3-13/16 in.
Volume: 42 cu. in.
Wall Box

Carton Quantity: 24
Carton Weight: 23 lb.

UPC: 085339129066
UNSPSC: 39121309
Patents:
U.S. Patent No. 6,908,003 B2
Country of Origin: United States of America

FEATURES

Machine tapped holes for 2-position device ,
internal metal clamp for easy wire adjustment,
offset gauge marks, leveling ribs, rigid hard box
construction, no distortion with high
temperatures, shatter resistant with low
temperatures

APPLICATION

New work residential construction 2 HR fire
resistive walls - air tight

STANDARDS

ANSI / UL 514C: File No. E30594



NEMA OS 4 - Energy Efficient Air-Sealed Boxes for Electrical Applications



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's
CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Angled mid nails with fether ring nails

ADDITIONAL MATERIALS

Carbon steel fasteners

Plated carbon steel clamp and fasteners

Polyurethane flange