

Sealing Locknut

Size Range: 1/2" - 4"

Product Series: SL Industrial Sealing Locknut with Captive Molded Gasket

Materials: Steel Construction and PVC Molded Gasket

Zinc Plated

Made in the USA * Except as noted below

Precisioned Stamped with Cut Threads

Will Not Distor or Crack Under Load
Stays Flat for Full Bonding to Box

Provides Liquid Tight Seal Tight Protection



Industrial SPEC-grade

Steel Locknut With PVC Gasket
Provides Raintight Seal When
Fastening Threaded Conduit to
Non-threaded Entry In an Enclosure
or Box. Can Be Used on Threaded
Fittings for Environmental Seal.



Cat. # *	Trade Size "	Unit Carton	Std Pkg.	Wt. /c	A	B
SL1	1/2	100	1000	1	1.13	.13
SL2	3/4	100	1000	2	1.38	.14
SL3	1	50	500	4	1.72	.18
SL4	1-1/4	50	500	7	2.06	.19
SL5	1-1/2	25	250	8	2.38	.18
SL6	2	25	250	9	2.89	.19
SL7 *	2 1/2	-	30	29	3.54	.39
SL8 *	3	-	25	42	4.23	.39
SL9 *	3 1/2	-	10	48	4.75	.39
SL10 *	4	-	10	52	5.29	.39

Compliances:

Certified Made in the USA *

UL 514B *

NEMA Standard FB1

Federal Standard A-A-50553

CSA Standard: C22.2 No. 18F

RoHS Compliant

REACH Compliant

CA Prop 65 Compliant

UNSPSC 39121311



Available OPTIONS:

Heavy Duty Bonding Locknuts HDI Series

Heavy Duty True Tight Grounding Locknuts AH Series

LN Series of Industrial Grade Locknut .

* 2-1/2" to 4" are not UL Listed and do not meet BAA or Made in USA.

If This is Required, Use AMFICO HDI Series Locknuts Full Steel, UL, Made in USA with an SW Sealing Washer