



4-11/16" Square Boxes


With Conduit Knockouts




4SJ-3/4
1-1/2" Deep, Welded




4SJ-EK
1-1/2" Deep, Welded




4SJD-3/4
2-1/8" Deep, Welded




4SJD-EK
2-1/8" Deep, Welded




4SJD-3/4-1
2-1/8" Deep, Welded



4SJD-1
2-1/8" Deep, Welded



4SJD-1-1/4
2-1/8" Deep, Welded



4SPJD
Plenum Box 2-1/8" Deep,
Drawn
(Screws supplied with cover,
catalog number 8487P)

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Sides	Knockout Description	Ends	Bottom	Wt. Lbs. Per 100	Std. Pkg.
4SJ-3/4 (72151-3/4)	1-1/2	29.5	(8)3/4"	--	(2)1/2"	(2)3/4"	87.0	25
4SJ-EK (72151-SPL)	1-1/2	29.5	(10)Eccentric KO	--	(1)1/2"	(1)3/4" (2)Eccentric KO	88.0	25
4SJD-3/4	2-1/8	42.0	(10)3/4"	--	(2)1/2"	(2)3/4"	104.0	25
4SJD-EK (72171-SPL)	2-1/8	42.0	(12)Eccentric KO	--	(1)1/2"	(1)3/4" (2)Eccentric KO	104.0	25
4SJD-3/4-1 (72171-3/4-1-SPL)	2-1/8	42.0	(4)3/4" (4)1"	--	(2)1/2"	(2)3/4"	108.0	25
4SJD-1 (72171-1)	2-1/8	42.0	(8)1"	--	(2)1/2"	(2)3/4"	97.0	25
4SJD-1-1/4 (72171-1-1/4)	2-1/8	42.0	(6)1-1/4"	--	(2)1/2"	(2)3/4"	106.0	25
4SPJD	2-1/8	42.0	(4)1/2" (6)3/4"	--	(3)1/2"	(2)3/4"	108.0	25




**Groundskeeper
Raised ground**
feature on boss inside box
provides two #10-32 tapped
hole, allowing one or two 3/8"
long green ground screws to
be threaded into box without
contacting mounting surface.
Other boxes provided with flat
ground tapped hole, except
Plenum Boxes. See OB/SB-1
page 49 for ground screws,
pigtails and accessories.

OB/SB-1




4-11/16" Square Boxes

With Conduit Knockouts



4SJD-EK-VB
2-1/8" Deep, Welded
Offset vertical bracket flush
with front of box



4SJD-1-VB
2-1/8" Deep, Welded
Offset vertical bracket
flush with front of box




Groundskeeper
Raised ground
feature on boss inside box
provides two #10-32 tapped
hole, allowing one or two
3/8" long green ground
screws to be threaded
into box without contact-
ing mounting surface. See
OB/SB-1 page 49 for ground
screws, pigtails and
accessories.


Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description Sides Ends Bottom	Wt. Lbs. Per 100	Std. Pkg.
4SJD-EK-VB	2-1/8	42.0	(9)Eccentric KO -- (1)1/2" (1)3/4" (2)Eccentric KO	124.0	25
4SJD-1-VB	2-1/8	42.0	(6)1" -- (2)1/2" (2)3/4"	124.0	25

4-11/16" Square Box Extension Rings

With Conduit Knockouts



4SJDE-1/2-3/4
2-1/8" Deep, Drawn
8-32 tapped holes and slide-on
screw slots in bottom




4SJDE-1
2-1/8" Deep, Drawn
8-32 tapped holes and slide-on
screw slots in bottom

Catalog Number	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description Sides Ends Bottom	Wt. Lbs. Per 100	Std. Pkg.
4SJDE-1/2-3/4	2-1/8	42.0	(4)1/2" -- -- (6)3/4"	66.0	25
4SJDE-1	2-1/8	42.0	(8)1" -- --	66.0	25




4-11/16" Square Covers


Raised Surface




8484
1/2" Raised




8484A
1/2" Raised




8484BN
1/2" Raised




8489
1/2" Raised



8490
1/2" Raised



8491N
1/2" Raised



8495
1/2" Raised

Catalog Number	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs. Per 100	Std. Pkg.
8484	1/2	10.0	One GFCI Device	50.0	10
8484A	1/2	10.0	One Toggle Switch, One GFCI Device	50.0	10
8484BN	1/2	10.0	One Duplex Receptacle, One GFCI Device*	45.0	10
8489	1/2	10.0	One Toggle Switch	54.0	10
8490	1/2	10.0	Two Toggle Switches	54.0	10
8491N	1/2	10.0	One Duplex Receptacle*	50.0	10
8495	1/2	10.0	Blank	55.0	10


*Extra mounting screws and nuts provided.

OB/SB-1




4-11/16" Square Covers


Raised Surface




8492N
1/2" Raised




8493N
1/2" Raised




8494
1/2" Raised
1-13/32" Opening




8496
1/2" Raised
1-19/32" Opening



8497
1/2" Raised
1-3/4" Opening



8498
1/2" Raised
2-5/32" Opening



8499
1/2" Raised
2-1/2" Opening


Catalog Number	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs. Per 100	Std. Pkg.
8492N	1/2	10.0	Two Duplex Receptacles*	45.0	10
8493N	1/2	10.0	One Toggle Switch, One Duplex Receptacle*	50.0	10
8494	1/2	10.0	Single Receptacle 1-13/32" D	54.0	10
8496	1/2	10.0	Single Receptacle 1-19/32" D	54.0	10
8497	1/2	10.0	Twist Lock Receptacle 1-3/4" D	51.0	10
8498	1/2	10.0	Single Receptacle 2-5/32" D	54.0	10
8499	1/2	10.0	Single Receptacle 2-1/2" D	54.0	10

*Extra mounting screws and nuts provided.




4-11/16" Square Covers


Flat and Single Device – Ceiling Plaster Rings/Mud Rings




8487
Flat




8487K
Flat




8487P
Plenum box cover
with gasket and screws




8488A
1/2" Raised




8488B
5/8" Raised



8488C
3/4" Raised



8488D
1" Raised




8488E
1-1/4" Raised

OB/SB-1


Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs. Per 100	Std. Pkg.
8487 (72C1)	Flat	—	Blank	42.0	50
8487K (72C6)	Flat	—	One 1/2" Knockout	43.0	50
8487P	Flat	—	Blank Neoprene Gasketed with Four Captive Screws	48.0	50
Single Device					
8488A	1/2	3.0	Ears 2-3/4" C to C	36.0	25
8488B	5/8	4.0	Ears 2-3/4" C to C	42.0	25
8488C	3/4	5.0	Ears 2-3/4" C to C	48.0	25
8488D	1	7.0	Ears 2-3/4" C to C	60.0	25
8488E	1-1/4	9.0	Ears 2-3/4" C to C	72.0	25

4-11/16" Square Covers


Single Device – Plaster Rings/Mud Rings




8485B
1/4" Raised




8485A
1/2" Raised




8485C
5/8" Raised



8485
3/4" Raised



8485D
1" Raised




8485E
1-1/4" Raised

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs. Per 100	Std. Pkg.
8485B	1/4	2.5	Single Device	34.0	25
8485A (72C13)	1/2	4.0	Single Device	38.0	25
8485C	5/8	4.8	Single Device	39.0	25
8485 (72C14)	3/4	5.5	Single Device	40.0	25
8485D	1	6.3	Single Device	45.0	10
8485E	1-1/4	8.0	Single Device	50.0	10




4-11/16" Square Covers


Double Device – Plaster Rings/Mud Rings




8486F
Flat




8486B
1/4" Raised




8486A
1/2" Raised




8486C
5/8" Raised



8486
3/4" Raised



8486D
1" Raised




8486E
1-1/4" Raised

OB/SB-1


Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs. Per 100	Std. Pkg.
8486F	Flat	0.0	Double Device	11.0	25
8486B	1/4	2.8	Double Device	12.0	25
8486A (72C17)	1/2	7.5	Double Device	30.0	25
8486C	5/8	6.8	Double Device	32.0	25
8486	3/4	8.5	Double Device	36.0	25
8486D	1	11.3	Double Device	40.0	10
8486E	1-1/4	13.5	Double Device	50.0	10

4-11/16" Square Tile Covers


Single Device and Double Device - Plaster Rings/Mud Rings




856-100
1" Raised




856-125
1-1/4" Raised




856-150
1-1/2" Raised




856-200
2" Raised



857-100
1" Raised



857-150
1-1/2" Raised



857-200
2" Raised

Catalog Number	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs. Per 100	Std. Pkg.
Single Device					
856-100	1	6.8	Single Device	42.0	10
856-125	1-1/4	9.5	Single Device	48.0	10
856-150	1-1/2	11.3	Single Device	54.0	10
856-200	2	15.0	Single Device	66.0	10
Double Device					
857-100	1	12.5	Double Device	40.0	10
857-150	1-1/2	18.8	Double Device	54.0	10
857-200	2	24.5	Double Device	70.0	10