







4-11/16" Square Boxes

With Knockouts

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

Commercial Products

COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description			Wt. Lbs./Kgs. Per 100	
				Sides	Ends	Bottom		
 1-1/2" Deep, Welded	4SJ-3/4 (72151-3/4)	1-1/2	29.5	(8) 3/4"	—	(2) 1/2" (2) 3/4"	87.0/ 39.46	
 1-1/2" Deep, Welded	4SJ-EK (72151-SPL)	1-1/2	29.5	(10) Eccentric KO	—	(1) 1/2" (1) 3/4" (2) Eccentric KO	88.0/ 39.92	
 1-1/2" Deep, Welded	4SJ-EKP †	With Green Ground Wire	1-1/2	29.5	(10) Eccentric KO	—	(1) 1/2" (1) 3/4" (2) Eccentric KO	88.0/ 39.92
 2-1/8" Deep, Welded	4SJD-3/4 (72171-3/4)		2-1/8	42.0	(10) 3/4"	—	(2) 1/2" (2) 3/4"	104.0/ 47.17
 2-1/8" Deep, Welded	4SJD-EK (72171-SPL)		2-1/8	42.0	(12) Eccentric KO	—	(1) 1/2" (1) 3/4" (2) Eccentric KO	104.0/ 47.17
	4SJD-EKRD *	Red Box Option	2-1/8	42.0	(12) Eccentric KO	—	(1) 1/2" (1) 3/4" (2) Eccentric KO	104.0/ 47.17
 2-1/8" Deep, Welded	4SJD-EKP †	With Green Ground Wire	2-1/8	42.0	(12) Eccentric KO	—	(1) 1/2" (1) 3/4" (2) Eccentric KO	104.0/ 47.17

* For fire alarm circuits. Red powder coat finish.

† Provided with green ground screw and 10" long No. 12 AWG solid, insulated green ground wire.

1516

 **Appleton®**





Visit our website at www.appletonelec.com or contact us at (800) 621-1506.

© September 2010

4-11/16" Square Boxes

With Knockouts

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description			Wt. Lbs. /Kgs. Per 100
				Sides	Ends	Bottom	
 2-1/8" Deep, Welded	4SJD-3/4-1 (72171-3/4-1-SPL)	2-1/8	42.0	(4) 3/4" (4) 1"	—	(2) 1/2" (2) 3/4"	108.0/ 48.99
 2-1/8" Deep, Welded	4SJD-1 (72171-1)	2-1/8	42.0	(8) 1"	—	(2) 1/2" (2) 3/4"	97.0/ 43.99
 2-1/8" Deep, Welded	4SJD-1-1/4 (72171-1-1/4)	2-1/8	42.0	(6) 1-1/4"	—	(2) 1/2" (2) 3/4"	106.0/ 48.08
 Plenum Box 2-1/8" Deep, Drawn (Screws supplied with cover, catalog number 8487P)	4SPJD	2-1/8	42.0	(4) 1/2" (6) 3/4"	—	(3) 1/2" (2) 3/4"	108.0/ 48.99

Commercial Products

COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS






4-11/16" Square Boxes and Extension Rings

With Knockouts

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

Commercial Products

COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS








		Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description			Wt. Lbs./ Kgs. Per 100
					Sides	Ends	Bottom	
4-11/16" Square Boxes								
		4SJD-EK-VB	2-1/8	42.0	(9) Eccentric KO	—	(1) 1/2" (1) 3/4" (2) Eccentric KO	124.0/ 56.25
	2-1/8" Deep, Welded Offset vertical bracket flush with front of box							
		4SJD-1-VB	2-1/8	42.0	(6) 1"	—	(2) 1/2" (2) 3/4"	124.0/ 56.25
	2-1/8" Deep, Welded Offset vertical bracket flush with front of box							
4-11/16" Square Box Extension Rings								
		4SJDE-1/2-3/4	2-1/8	42.0	(4) 1/2" (6) 3/4"	—	—	66.0/ 29.94
	2-1/8" Deep, Drawn 8-32 tapped holes and slide- on screw slots in bottom	4SJDE-1/2-3/4RD *	Red Box Option	2-1/8	42.0	(4) 1/2" (6) 3/4"	—	66.0/ 29.94
		4SJDE-1	2-1/8	42.0	(8) 1"	—	—	66.0/ 29.94
	2-1/8" Deep, Drawn 8-32 tapped holes and slide- on screw slots in bottom							

* For fire alarm circuits. Red powder coat finish.

4-11/16" Square Covers

Raised Surface

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs./Kgs. Per 100
 1/2" Raised	8484	1/2	10.0	One GFCI Device	50.0/ 22.68
 1/2" Raised	8484A	1/2	10.0	One Toggle Switch, One GFCI Device	50.0/ 22.68
 1/2" Raised	8484BN	1/2	10.0	One Duplex Receptacle, One GFCI Device *	45.0/ 20.41
 1/2" Raised	8489	1/2	10.0	One Toggle Switch	54.0/ 24.49
 1/2" Raised	8490	1/2	10.0	Two Toggle Switches	54.0/ 24.49
 1/2" Raised	8491N	1/2	10.0	One Duplex Receptacle *	50.0/ 22.68
 1/2" Raised	8495	1/2	10.0	Blank	55.0/ 24.95

* Extra mounting screws and nuts provided.








4-11/16" Square Covers

Raised Surface

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

Commercial Products

COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS







	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs./Kgs. Per 100
 1/2" Raised	8492N	1/2	10.0	Two Duplex Receptacles *	45.0/ 20.41
 1/2" Raised	8493N	1/2	10.0	One Toggle Switch, One Duplex Receptacle *	50.0/ 22.68
 1/2" Raised; 1-13/32" Opening	8494	1/2	10.0	Single Receptacle 1-13/32" D	54.0/ 24.49
 1/2" Raised; 1-19/32" Opening	8496	1/2	10.0	Single Receptacle 1-19/32" D	54.0/ 24.49
 1/2" Raised; 1-3/4" Opening	8497	1/2	10.0	Twist Lock Receptacle 1-3/4" D	51.0/ 23.13
 1/2" Raised; 2-5/32" Opening	8498	1/2	10.0	Single Receptacle 2-5/32" D	54.0/ 24.49
 1/2" Raised; 2-1/2" Opening	8499	1/2	10.0	Single Receptacle 2-1/2" D	54.0/ 24.49

* Extra mounting screws and nuts provided.

4-11/16" Square Covers

Flat and Single - Ceiling Plaster Rings/Mud Rings

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs. /Kgs. Per 100
Flat					
	8487 (72C1)	Flat	—	Blank	42.0/ 19.05
	8487RD *	Red Box Option	Flat	Blank	42.0/ 19.05
	8487K (72C6)	Flat	—	One 1/2" Knockout	43.0/ 19.50
	8487P	Flat	—	Blank Plenum Box Cover Gasketed with Four Captive Screws	48.0/ 21.77
Single Device					
 1/2" Raised	8488A	1/2	3.0	Ears 2-3/4" C to C	36.0/ 16.33
 5/8" Raised	8488B	5/8	4.0	Ears 2-3/4" C to C	42.0/ 19.05
 3/4" Raised	8488C	3/4	5.0	Ears 2-3/4" C to C	48.0/ 21.77

* For fire alarm circuits. Red powder coat finish.



4-11/16" Square Covers

Single Device - Ceiling Plaster Rings/Mud Rings

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

Commercial Products







COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs./Kgs. Per 100
 1" Raised	8488D	1	7.0	Ears 2-3/4" C to C	60.0/ 27.22
 1-1/4" Raised	8488E	1-1/4	9.0	Ears 2-3/4" C to C	72.0/ 32.66

4-11/16" Square Covers

Single Device - Plaster Rings/Mud Rings

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs./Kgs. Per 100
 1/4" Raised	8485B	1/4	2.5	Single Device	34.0/ 15.42
 1/2" Raised	8485A (72C13)	1/2	4.0	Single Device	38.0/ 17.24
 5/8" Raised	8485C	5/8	4.8	Single Device	39.0/ 17.69
 3/4" Raised	8485 (72C14)	3/4	5.5	Single Device	40.0/ 18.14
 1" Raised	8485D	1	6.3	Single Device	45.0/ 20.41
 1-1/4" Raised	8485E	1-1/4	8.0	Single Device	50.0/ 22.68

Commercial Products

COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS








4-11/16" Square Covers

Double Device - Plaster Rings/Mud Rings

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

Commercial Products








COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs./Kgs. Per 100
 Flat	8486F	Flat	0.0	Double Devices	11.0/ 4.99
 1/4" Raised	8486B	1/4	2.8	Double Devices	12.0/ 5.44
 1/2" Raised	8486A (72C17)	1/2	7.5	Double Devices	30.0/ 13.61
 5/8" Raised	8486C	5/8	6.8	Double Devices	32.0/ 14.52
 3/4" Raised	8486	3/4	8.5	Double Devices	36.0/ 16.33
 1" Raised	8486D	1	11.3	Double Devices	40.0/ 18.14
 1-1/4" Raised	8486E	1-1/4	13.5	Double Devices	50.0/ 22.68

4-11/16" Square Tile Covers

Single Device and Double Device - Plaster Rings/Mud Rings

UL Standard: 514A
UL Listed: E2527
NEMA: OS-1

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	Wt. Lbs./Kgs. Per 100
Single Device					
 1" Raised	856-100	1	6.8	Single Device	42.0/ 19.05
 1-1/4" Raised	856-125	1-1/4	9.5	Single Device	48.0/ 21.77
 1-1/2" Raised	856-150	1-1/2	11.3	Single Device	54.0/ 24.49
 2" Raised	856-200	2	15.0	Single Device	66.0/ 29.94
Double Device					
 1" Raised	857-100	1	12.5	Double Devices	40.0/ 18.14
 1-1/2" Raised	857-150	1-1/2	18.8	Double Devices	54.0/ 24.49
 2" Raised	857-200	2	24.5	Double Devices	70.0/ 31.75

Commercial Products

COMMERCIAL PRODUCTS: SWITCH AND OUTLET BOXES AND COVERS