



4-11/16" Square Boxes


With Conduit Knockouts




4SJ-3/4
1-1/2" Deep, Welded




4SJ-EK
1-1/2" Deep, Welded




4SJD-3/4
2-1/8" Deep, Welded




4SJD-EK
2-1/8" Deep, Welded




4SJD-3/4-1
2-1/8" Deep, Welded



4SJD-1
2-1/8" Deep, Welded



4SJD-1-1/4
2-1/8" Deep, Welded



4SPJD
Plenum Box 2-1/8" Deep,
Drawn
(Screws supplied with cover,
catalog number 8487P)

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Sides	Knockout Description	Wt. Lbs. Per 100	Std. Pkg.
Ends	Bottom					
4SJ-3/4 (72151-3/4)	1-1/2	29.5	(8)3/4"	--	(2)1/2" (2)3/4"	87.0 25
4SJ-EK (72151-SPL)	1-1/2	29.5	(10)Eccentric KO	--	(1)1/2" (1)3/4" (2)Eccentric KO	88.0 25
4SJD-3/4	2-1/8	42.0	(10)3/4"	--	(2)1/2" (2)3/4"	104.0 25
4SJD-EK (72171-SPL)	2-1/8	42.0	(12)Eccentric KO	--	(1)1/2" (1)3/4" (2)Eccentric KO	104.0 25
4SJD-3/4-1 (72171-3/4-1-SPL)	2-1/8	42.0	(4)3/4" (4)1"	--	(2)1/2" (2)3/4"	108.0 25
4SJD-1 (72171-1)	2-1/8	42.0	(8)1"	--	(2)1/2" (2)3/4"	97.0 25
4SJD-1-1/4 (72171-1-1/4)	2-1/8	42.0	(6)1-1/4"	--	(2)1/2" (2)3/4"	106.0 25
4SPJD	2-1/8	42.0	(4)1/2" (6)3/4"	--	(3)1/2" (2)3/4"	108.0 25




Groundskeeper
Raised ground
feature on boss inside box
provides two #10-32 tapped
hole, allowing one or two 3/8"
long green ground screws to
be threaded into box without
contacting mounting surface.
Other boxes provided with flat
ground tapped hole, except
Plenum Boxes. See OB/SB-1
page 49 for ground screws,
pigtails and accessories.

OB/SB - 1




4-11/16" Square Boxes

With Conduit Knockouts



4SJD-EK-VB
2-1/8" Deep, Welded
Offset vertical bracket flush
with front of box



4SJD-1-VB
2-1/8" Deep, Welded
Offset vertical bracket
flush with front of box




Groundskeeper
Raised ground
feature on boss inside box
provides two #10-32 tapped
hole, allowing one or two
3/8" long green ground
screws to be threaded
into box without contact-
ing mounting surface. See
OB/SB-1 page 49 for ground
screws, pigtails and
accessories.


Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Sides	Description Ends Bottom	Wt. Lbs. Per 100	Std. Pkg.
4SJD-EK-VB	2-1/8	42.0	(9)Eccentric KO	-- (1)1/2" (1)3/4" (2)Eccentric KO	124.0	25
4SJD-1-VB	2-1/8	42.0	(6)1"	-- (2)1/2" (2)3/4"	124.0	25

4-11/16" Square Box Extension Rings

With Conduit Knockouts



4SJDE-1/2-3/4
2-1/8" Deep, Drawn
8-32 tapped holes and slide-on
screw slots in bottom



4SJDE-1
2-1/8" Deep, Drawn
8-32 tapped holes and slide-on
screw slots in bottom

Catalog Number	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Sides	Description Ends Bottom	Wt. Lbs. Per 100	Std. Pkg.
4SJDE-1/2-3/4	2-1/8	42.0	(4)1/2" (6)3/4"	-- --	66.0	25
4SJDE-1	2-1/8	42.0	(8)1"	-- --	66.0	25