


OB/SB - 1



4" Square Boxes - 1-1/2" Deep


With Conduit Knockouts

OB/SB - 1




4SVB-3/4PL

1-1/2" Deep, Welded
Plain vertical bracket




4SVB-EK-PL

1-1/2" Deep, Welded
Plain vertical bracket




4SOB-EK

1-1/2" Deep, Welded
1-3/8 Offset vertical bracket



4SAB-EK

1-1/2" Deep, Welded
Vertical bracket
with barbed hooks



4SB-EK

1-1/2" Deep, Welded
Stud NL bracket set flush
with front of box

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Sides	Description Ends	Bottom	Wt. Lbs. Per 100	Std. Pkg.
4SVB3/4PL (52151-V-3/4)	1-1/2	21.0	(6)3/4"	--	(2)1/2" (2)3/4"	81.0	25
4SVB-EK-PL	1-1/2	21.0	(6)1/2"	--	(2)1/2"	81.0	25
			(3)Eccentric KO		(2)Eccentric KO		
4SOB-EK	1-1/2	21.0	(6)1/2"	--	(2)1/2"	89.0	25
			(3)Eccentric KO		(2)Eccentric KO		
4SAB-EK	1-1/2	21.0	(6)1/2"	--	(2)1/2"	82.0	25
			(3)Eccentric KO		(2)Eccentric KO		
4SB-EK (52151-B-1/2)	1-1/2	21.0	(6)1/2"	--	(2)1/2"	78.0	25
			(3)Eccentric KO		(2)Eccentric KO		



Groundskeeper

Raised ground feature

on boss inside box provides one #10-32
tapped hole, allowing a 3/8" long green
ground screw to be threaded into box
without contacting mounting surface.
Other boxes provided with flat ground
tapped hole, except Plenum Boxes.
See OB/SB-1 page 49 for ground
screws, pigtails and accessories.