




Conduit Bushings for Rigid Metal Conduit and IMC



Catalog No.	Size (In.)	Dimensions in Inches		Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
		A	B			
Threaded Bushings– Malleable Iron, Zinc Electroplated						
BU50	1/2	1-1/32	3/8	3	100	1000
BU75	3/4	1-1/4	7/16	4	100	1000
BU100	1	1-9/16	1/2	7	50	500
BU125	1-1/4	2	5/8	13	50	200
BU150	1-1/2	2-5/32	5/8	14	50	200
BU200	2	2-5/8	5/8	19	25	100
BU250	2-1/2	3-3/16	3/4	43	5	25
BU300	3	3-13/16	15/16	56	5	25
BU350	3-1/2	4-7/16	15/16	76	5	25
BU400	4	4-15/16	1-1/16	109	5	25
BU500	5	6	1-3/16	144	-	10
BU600	6	7-3/8	1-5/16	243	-	5



Threaded Bushings– Insulated– 150°C Temperature Rating– Malleable Iron, Zinc Electroplated						
BU50I	1/2	1-3/16	1/2	4	100	1000
BU75I	3/4	1-7/16	9/16	6	100	1000
BU100I	1	1-3/4	5/8	9	50	500
BU125I	1-1/4	2-1/8	3/4	10	50	200
BU150I	1-1/2	2-5/16	7/8	19	25	100
BU200I	2	2-13/16	15/16	24	25	100
BU250I	2-1/2	3-3/8	1	47	5	25
BU300I	3	4-1/16	1-1/8	60	5	25
BU350I	3-1/2	4-1/2	1-3/16	69	5	25
BU400I	4	5-3/16	1-5/16	100	2	20
BU500I	5	6-1/16	1-5/16	200	-	10
BU600I	6	7-1/4	1-5/16	243	-	5




Threadless Bushings– Insulated– 150°C Temperature Rating– Malleable Iron, Zinc Electroplated						
BU50SI	1/2	1-3-16	1/2	4	100	1000
BU75SI	3/4	1-7/16	9-1/16	6	100	1000
BU100SI	1	1-3/4	5/8	9	50	500
BU125SI	1-1/4	2-1/8	3/4	10	50	200
BU150SI	1-1/2	2-5/16	7/8	18	25	100
BU200SI	2	2-13/16	15/16	25	25	100
BU250SI	2-1/2	3-3/8	1	40	5	25
BU300SI	3	4-1/16	1-1/8	55	5	25
BU350SI	3-1/2	4-1/2	1-3/16	59	5	25
BU400SI	4	5-3/16	1-5/16	90	2	20



Threaded Capped Bushings– Malleable Iron, Zinc Electroplated, Polyethylene Cap						
BUC50	1/2	1-1/32	3/8	3	100	1000
BUC75	3/4	1-1/4	7/16	5	100	1000
BUC100	1	1-9/16	1/2	8	50	500
BUC125	1-1/4	2	5/8	12	50	200
BUC150	1-1/2	2-5/32	5/8	17	10	100
BUC200	2	2-5/8	5/8	20	10	100
BUC250	2-1/2	3-3/16	3/4	40	5	50
BUC300	3	3-13/16	15/16	52	5	25
BUC350	3-1/2	4-7/16	15/16	76	5	25
BUC400	4	4-15/16	1-1/16	114	5	20
BUC500	5	6	1-3/16	149	-	10
BUC600	6	7-3/8	1-5/16	250	-	5

Conduit Bushings for Rigid Metal Conduit and IMC



Catalog No.	Size (In.)	Dimensions in Inches		Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
		A	B			
Threaded Impact Resistant Plastic Bushing– 105°C Temperature Rating						
BBU50	1/2	1-1/16	13/32	0.6	100	400
BBU75	3/4	1-5/16	13/32	0.8	100	400
BBU100	1	1-9/16	9/16	1.5	50	200
BBU125	1-1/4	1-29/32	9/16	2.3	25	100
BBU150	1-1/2	2-3/16	9/16	3.0	25	100
BBU200	2	2-11/16	5/8	4.0	25	50
BBU250	2-1/2	3-3/16	23/32	7.8	10	20
BBU300	3	3-27/32	3/4	10.0	10	20
BBU350	3-1/2	4-11/32	3/4	13.0	5	10
BBU400	4	4-27/32	25/32	11.0	5	10
Threaded Self-extinguishing Thermoplastic Bushing– 150°C Temperature Rating						
BBU50H	1/2	1-1/16	13/32	0.8	100	400
BBU75H	3/4	1-5/16	13/32	0.9	100	400
BBU100H	1	1-9/16	9/16	1.8	50	200
BBU125H	1-1/4	1-29/32	9/16	2.8	25	100
BBU150H	1-1/2	2-3/16	9/16	3.3	25	100
BBU200H	2	2-11/16	5/8	4.4	25	50
BBU250H	2-1/2	3-3/16	23/32	14.3	10	20
BBU300H	3	3-27/32	3/4	11.0	10	20
BBU350H	3-1/2	4-11/32	3/4	14.3	5	10
BBU400H	4	4-27/32	25/32	18.7	5	10