

Handy Box Covers

For 3-3/4" x 1-1/2", 4" x 2-1/8" and 4-1/8" x 2-3/8" Boxes

Catalog Number (Universal No.)	Description	Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
For 3-3/4" x 1-1/2" Boxes				
2520 (48C1)	Blank	12.0	50	100



2520

Catalog Number (Universal No.)	Description	Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
For 4" x 2-1/8" Boxes				
2540 (58C1)	Blank	11.0	25	100
2555 (58C6)	One 1/2" Knockout	18.0	25	100
2538 (58C4)	Single Receptacle 1-19/32" D	10.0	25	100
2539 (58C5)	Single Receptacle 1-13/32" D	10.0	25	100
2510 (58C7)	Duplex Receptacle	8.0	25	100
2594 (58C30)	One Toggle Switch	10.0	25	100



2540



2555



2538



2539



2510



2594

Catalog Number (Universal No.)	Description	Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
For 4-1/8" x 2-3/8" Boxes				
180A (68C-1)	Blank	13.0	25	100
180T (68C-30)	One Toggle Switch	12.0	25	100
180G	GFI Receptacle	9.0	25	100
180W (68C-7)	Duplex Receptacle	9.0	25	100
180X (68C-5)	Single Receptacle 1-13/32" D	10.0	25	100



180A



180T



180G




180W




180X

Handy Boxes


3-3/4" x 1-1/2" and 4" x 2-1/8" with Conduit Knockouts




4SS
1-1/2" Deep, Drawn




4CSL-1/2
1-1/4" Deep, Drawn




4SSLS-1/2
1-1/2" Deep, Drawn




 **4CS-1/2***
1-7/8" Deep, Drawn




 **4CS-3/4**
1-7/8" Deep, Drawn




 **4CSVB-1/2**
1-7/8" Deep, Drawn
Plain vertical bracket
set back 5/8"




4CSX-1/2PL
1-7/8" Deep, Drawn
Plain vertical angle
bracket, set back 5/8"




 **4SSL-1/2**
2-1/8" Deep, Welded



 **4SSL-1/2DR***
2-1/8" Deep, Drawn



4SSL-3/4
2-1/8" Deep, Welded



 **4SSL3/4-DR**
2-1/8" Deep, Drawn




Groundskeeper™
Raised ground feature
on boss inside box provides one
#10-32 tapped hole, allowing a 3/8"
long green ground screw to be
threaded into box without contacting
mounting surface. Other boxes
provided with flat ground tapped
hole, except Plenum Boxes. See
OB/SB-1 page 49 for ground screws,
pigtaills and accessories.

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Sides	Description Ends	Bottom	Wt. Lbs. Per 100	Std. Pkg.
3-3/4" x 1-1/2" With Conduit Knockouts							
4SS	1-1/2	7.0	(6)1/2"	(2)1/2"	(3)1/2"	34.0	50
4" x 2-1/8" With Conduit Knockouts							
4CSL-1/2 (58361-1/2)	1-1/4	9.5	(6)1/2"	(2)1/2"	(3)1/2"	39.0	50
4SSLS-1/2 (58351-1/2)	1-1/2	10.3	(6)1/2"	(2)1/2"	(3)1/2"	46.0	50
4CS-1/2* (58361-1/2)	1-7/8	13.0	(6)1/2"	(2)1/2"	(2)1/2"	52.0	50
4CS-3/4 (58361-3/4)	1-7/8	13.0	(4)3/4"	(2)3/4"	(1)3/4"	49.0	50
4CSVB-1/2 (58361-F1/2)	1-7/8	13.0	(3)1/2"	(2)1/2"	(2)1/2"	65.0	50
4CSX-1/2PL (58361-A1/2)	1-7/8	13.0	(3)1/2"	(2)1/2"	(3)1/2"	66.0	50
4SSL-1/2 (58371-1/2)	2-1/8	14.5	(6)1/2"	(2)1/2"	(2)1/2"	54.0	50
4SSL1/2-DR* (58371-1/2)	2-1/8	14.5	(6)1/2"	(2)1/2"	(2)1/2"	54.0	50
4SSL-3/4 (58371-3/4)	2-1/8	14.5	(4)3/4"	(2)3/4"	(2)3/4"	54.0	50
4SSL3/4-DR (58371-3/4)	2-1/8	14.5	(4)3/4"	(2)3/4"	(1)3/4"	54.0	50


* CSA-C

Handy Boxes


4" x 2-1/8" with Conduit Knockouts




4SSLVB-1/2
2-1/8" Deep, Welded
Plain vertical bracket
set back 3/4"




4SSLX-1/2PL
2-1/8" Deep, Welded
Plain vertical angle bracket
set back 5/8"



4SSLD-1/2
2-1/2" Deep, Drawn



4SSLE-1/2
1-1/2" Deep, Drawn



4CSE-1/2
1-7/8" Deep, Drawn

OB/SB-1

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Sides	Description Ends	Bottom	Wt. Lbs. Per 100	Std. Pkg.
With Conduit Knockouts							
4SSLVB-1/2 (58371-F1/2)	2-1/8	14.5	(3)1/2"	(2)1/2"	(2)1/2"	74.0	50
4SSLX-1/2PL	2-1/8	14.5	(3)1/2"	(2)1/2"	(2)1/2"	71.0	50
4SSLD-1/2 (58351-1/2)	2-1/2	18.3	(6)1/2"	(2)1/2"	(3)1/2"	63.0	50
Extension Ring for 4" x 2-1/8" Handy Box with Conduit Knockouts							
4SSLE-1/2 (59351)	1-1/2	10.3	(6)1/2"	(2)1/2"	-- With Slide on	36.0	50
4CSE-1/2 (59361-1/2)	1-7/8	13.0	(6)1/2"	(2)1/2"	-- With Slide on	48.0	50




Groundskeeper™

Raised ground feature


on boss inside box provides one #10-32 tapped hole, allowing a 3/8" long green ground screw to be threaded into box without contacting mounting surface. Other boxes provided with flat ground tapped hole, except Plenum Boxes. See OB/SB-1 page 49 for ground screws, pigtails and accessories.

Handy Boxes

4" Solid Gang with Conduit Knockouts



133APFB-1/2
2-1/2" Deep, Welded
Three Gang – 5-3/4" Wide
Plain offset side combination
bracket set back 1/2"




134APFB-1/2
2-1/2" Deep, Welded
Four Gang – 7-1/2" Wide
Stud NL bracket set back 1/2"


Catalog Number	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description			Wt. Lbs. Per 100	Std. Pkg.
			Sides	Ends	Bottom		
133APFB-1/2	2-1/2	44.5	(2) 1/2-3/4"	(6) 1/2-3/4"	(5) 1/2-3/4"	129.0	20
134APFB-1/2	2-1/2	58.0	(2) 1/2-3/4"	(8) 1/2-3/4"	(10) 1/2-3/4"	150.0	20

Handy Boxes


4-1/8" x 2-3/8" with Conduit Knockouts



 **180-1/2**
1-3/4" Deep, Drawn



 **181-1/2**
2-1/4" Deep, Drawn



184E
1-1/2" Deep, Drawn



Groundskeeper™
Raised ground feature

on boss inside box provides one #10-32 tapped hole, allowing a 3/8" long green ground screw to be threaded into box without contacting mounting surface. Other boxes provided with flat ground tapped hole, except Plenum Boxes. See OB/SB-1 page 49 for ground screws, pigtails and accessories.

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description			Wt. Lbs. Per 100	Std. Pkg.
			Sides	Ends	Bottom		
With Conduit Knockouts							
180-1/2 (68361-1/2)	1-3/4	15.0	(6)1/2"	(2)1/2"	(2)1/2"	54.0	50
181-1/2 (68371-1/2)	2-1/4	18.3	(6)1/2"	(2)1/2"	(2)1/2"	60.0	50
Extension Ring for 4-1/8" x 2-3/8"		Handy Box with Conduit Knockouts					
184E (69351)	1-1/2	13.5	(6)1/2"	(2)1/2"	-- With Slide on	39.0	50