

## Conduit Caps

Conduit cap and insulating bushing.



EMT50C




EMT75C


| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | UNIT PKG | STD PKG | DIM A | DIM B |
|----------------|--------------------------|------------|----------|---------|-------|-------|
| EMT50C         | 12203                    | 1/2        | 100      | 1000    | .531  | .840  |
| EMT75C         | 12204                    | 3/4        | 100      | 1000    | .531  | 1.056 |
| EMT100C        | 12207                    | 1          | 100      | 100     | .625  | 1.280 |
| EMT125C        | 12209                    | 1-1/4      | 100      | 100     | .625  | 1.660 |
| EMT150C        | 12211                    | 1-1/2      | 100      | 100     | .625  | 1.915 |
| EMT200C        | 12213                    | 2          | 50       | 50      | .625  | 2.377 |
| EMT250C*       | 12215                    | 2-1/2      | 25       | 25      | 1.225 | 3.062 |
| EMT300C*       | 12217                    | 3          | 25       | 25      | 1.225 | 3.690 |
| EMT350C*       | 12219                    | 3-1/2      | 25       | 25      | 1.231 | 4.187 |
| EMT400C*       | 12221                    | 4          | 25       | 25      | 1.233 | 4.815 |

Refer to page I-1 for Rigid Insulating Bushings size 1/2" through 4".

\*Can also be used for rigid, IMC, and PVC rigid conduit.



Use this capped version to seal off conduit during concrete pours. Then remove cap/seal with razor knife or use screwdriver to punch hole in cap. (EMT300C)



String can be used to aid removal.