

RIGID • IMC FITTINGS

Pipe Hangers

One-piece, non-metallic, UV rated.



NM2000



NM2080


Catalog Number	UPC/DCI/NAED MFG #01 8997	Rigid Size	EMT Size	LT Size	Flex Size	ENT Size	Copper Tubing	STD PKG	DIM A	DIM B	DIM C
NM1900†	54514	-	-	5/16	-	-	1/2	100	.870	.670	1.260
NM2000	54515	-	1/2	3/8	-	-	-	100	1.060	.770	1.390
NM2005	54525	1/2	-	1/2	1/2	1/2	-	100	1.270	.800	1.520
NM2010	54516	-	3/4	-	-	-	3/4	100	1.380	.790	1.610
NM2015	54526	3/4	-	3/4	3/4	3/4	-	100	1.410	.790	1.780
NM2020	54517	-	1	-	-	-	1	100	1.560	.800	1.930
NM2025	54518	1	-	1	1	1	-	100	1.760	.830	2.140
NM2030	54528	-	1-1/4	-	-	-	1-1/4	100	1.950	.830	2.340
NM2040	54519	1-1/4	1-1/2	-	-	-	1-1/2	100	2.090	.830	2.530
NM2045	54544	1-1/2	-	1-1/2	1-1/2	-	-	100	2.160	.870	2.970
NM2150†	54547	-	-	-	-	-	2	50	2.640	.910	3.100
NM2050	54520	2	2	2	2	-	-	50	3.020	.910	3.470
NM2060	54521	2-1/2	2-1/2	2-1/2	2-1/2	-	-	50	3.460	1.115	5.095
NM2070	54522	3	3	3	3	-	-	25	4.224	1.362	6.153
NM2080	54523	3-1/2	3-1/2	3-1/2	3-1/2	-	-	25	4.720	1.548	7.000
NM2090	54524	4	4	4	4	-	-	10	5.365	1.743	7.850

Rigid sizes also same for IMC and PVC.

†For plumbing. UL not applicable



E161207 LR49636



QuickLATCH

Use it anywhere you would use a pipe hanger!

Features and Benefits

- I Costs the same as a steel pipe hanger with bolt and nut.
- I Conduit snaps into place, locking automatically.
- I Accommodates thinwall, rigid conduit, or PVC conduit.
- I Saves 25 seconds per installation... about 14 cents at \$20 per hour labor rate.
- I Mounts horizontally or vertically.

Installation Instructions...

1. Mount to wall, strut, stud, or threaded rod up to 1/4-20.
2. Press pipe firmly into QuickLATCH to lock it in place
3. That's it!



To Remove...

Use a screwdriver to lift tab.



- l UV rated for outdoor application.
- l Corrosion resistant.