



## SNAP<sup>2</sup>IT<sup>®</sup> Connectors with Insulated Throat

Zinc die-cast. For MC/HCF steel and aluminum cable • AC/HCF steel and aluminum cable • Flexible metal conduit steel and aluminum (regular and reduced wall) • MC cable continuous corrugated aluminum • MCI-A steel and aluminum cable.

**New!**

| CATALOG NUMBER | UPC/DCI/NAED MFG #01 8997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | DIM D | CABLE RANGE |
|----------------|---------------------------|------------|---------|----------|---------|-------|-------|-------|-------|-------------|
| 3810AST        | 00385                     | 3/8        | 1/2     | 50       | 500     | 1.473 | 1.179 | .840  | .316  | .370-.490   |
| 4010AST†       | 40355                     | 3/8        | 1/2     | 50       | 500     | 1.473 | 1.244 | .840  | .404  | .405-.612   |
| 5010AST        | 00517                     | 1/2        | 1/2     | 25       | 250     | 2.210 | 1.514 | .840  | .614  | .590-.920   |
| 7510AST        | 55090                     | 3/4        | 3/4     | 25       | 25      | 2.496 | 1.709 | 1.058 | .828  | .895-1.110  |

†Provided with red tinted inside clip so you can differentiate a 3810AST from a 4010AST.

Refer to chart on page E-26 for a list of cable types.  
Refer to chart on page E-27 for MCI-A cable ranges.  
Concrete tight when taped.


SNAP-TITE<sup>®</sup> and SNAP<sup>2</sup>IT<sup>®</sup> products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page 6.

PATENT PENDING.



### Features and Benefits

- Installs as fast and costs the same as our other SNAP<sup>2</sup>IT fittings, but cable insertion is even easier!
- Simply snap the cable into the fitting and snap it into the box... no tools needed! The screw only holds the clip in place.
- Widest cable ranges – accommodates cable from 14/2 to 10/4.
- Super-secure – the angled, two-prong clip locks down on MC cable so there's no chance of pullout.
- Cable is removable. Simply loosen the screw on top.



3810AST



4010AST



5010AST



7510AST

### Easy cable insertion – Tight, secure hold!



**Back View**  
Note angled,  
two-prong  
clip



**Top View**  
Clip holds  
cable firmly  
in place



**FOR THE  
WIDEST TOTAL  
CABLE RANGES**