On Line Catalog



| | |
|---|---|
| BURNDY Catalog Number | KA34U |
| UPC Number | 781810370247 |
| Description | 4STR-500 DUAL RATED |
| Status | Active |
| Web Use | |
| BURNDY Product Line | |

| | |
|---|---|
| **Dimensional** | |
| Width (in) | 1.51 |
| Length (in) | 2.81 |
| Bolt Hole Size (in) | 0.38 |
| Thickness | 0.31 |
| D - in | 1.5 |
| Pad Width (in) | 1.52 |
| N (in) | 0.88 |
| **General** | |
| Number of Conductors | 1 |
| Number of Holes | 1 |
| Product Description | Aluminum Universal Terminal, 1 Hole, 4 AWG (Str)-500 kcmil, 3/8" Stud, 1 Screw, Al/Cu Rated, Tin Plated |
| **Conductor(s)** | |
| Aluminum Size (Range) | 4 AWG-500 kcmil |
| Copper Solid Size (Range) | N/A |
| Copper Stranded (Range) | 4 AWG-500 kcmil |
| **Physical** | |
| Installation Torque | 500 |
| Type of Plating | Tin |
| Connector Type | Terminal |
| Bolt Hole Size | 3/8 |
| Plated (Yes or No) | Y |
| Product Material | Aluminum |
| **Approvals / Certifications** | |
| Rated for Direct Burial | N |
| UL Listed | Y |
| CSA Certified | Y |
| ROHS Compatible | Exempt |
| UL Recognized | N |
| CULUS | N |
| Industry Standards | UL468A-468B |
| Documentation | |

For further technical assistance, please contact us

BURNDY LLC - USA BURNDY Technical Servcies Hours: 8.00 AM - 5.00 PM