Specifications



Photo is representative





Eaton BAF-15

Eaton Bussmann series BAF fuse, Fast acting, 15 A, Non-indicating, Ferrule end x ferrule end, 750 AIC at 250 Vac, 10 kAIC at 125 Vac, Nickel-plated brass endcaps, Standard, 250 V

General specifications

PRODUCT NAME	Eaton Bussmann series BAF fuse
CATALOG NUMBER	BAF-15
UPC	051712320153
PRODUCT LENGTH/DEPTH	1.5 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.25 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked
PRODUCT TYPE	Fuse

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	15 A
INTERRUPT RATING	750 AIC at 250 Vac 10 kAIC at 125 Vac
VOLTAGE RATING	250 V

Physical details

MATERIAL	Nickel-plated brass endcaps
PACKAGING TYPE	Standard

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Silver-plated fuse caps, replacement for "F15B" fuses

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BAF-15
TECHNICAL DATA SHEETS	BAF-15~BUSS MIDGET FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.