



| Part Number | Trade Size        | Length      | O.D.                     | I.D.                     |
|-------------|-------------------|-------------|--------------------------|--------------------------|
| V06ADA1     | $\frac{3}{8}$ "   | 100' Coil   | 0.690" Min<br>0.710" Max | 0.484" Min<br>0.504" Max |
| V06AEA1     | $\frac{1}{2}$ "   | 100' Coil   | 0.820" Min<br>0.840" Max | 0.622" Min<br>0.642" Max |
| V06AGA1     | $\frac{3}{4}$ "   | 100' Coil   | 1.030" Min<br>1.050" Max | 0.820" Min<br>0.840" Max |
| V06BAA1     | 1                 | 100' Coil   | 1.290" Min<br>1.315" Max | 1.041" Min<br>1.066" Max |
| V06BCN1     | 1 $\frac{1}{4}$ " | 50' Coil    | 1.630" Min<br>1.660" Max | 1.380" Min<br>1.410" Max |
| V06BEN1     | 1 $\frac{1}{2}$ " | 50' Coil    | 1.865" Min<br>1.900" Max | 1.575" Min<br>1.600" Max |
| V06CAN1     | 2"                | 50' Coil    | 2.340" Min<br>2.375" Max | 2.020" Min<br>2.045" Max |
| V06AEJ1     | $\frac{1}{2}$ "   | 1,000' Reel | 0.820" Min<br>0.840" Max | 0.622" Min<br>0.642" Max |
| V06AGM1     | $\frac{3}{4}$ "   | 700' Reel   | 1.030" Min<br>1.050" Max | 0.820" Min<br>0.840" Max |
| V06BAD1     | 1"                | 400' Reel   | 1.290" Min<br>1.315" Max | 1.041" Min<br>1.066" Max |

UL Listed (UL1660)  
 UL Category Code DXDQ  
 CSA Listed  
 For Use See NEC Article 356  
 Do not use PVC Cement with this product,  
 use only approved liquidtight fittings  
 May be used outdoors exposed to sunlight  
 May be directly buried  
 600 volt maximum  
 Minimum installation temperature 0.4°F (-18°C)  
 Maximum ambient temperature 167°F (75°C)  
 UL Rated: 80°C dry, 60°C wet, 70°C oil resistant  
 Product is TYPE B LFNC  
 Not plenum rated

Dimensions are nominal



**CANTEX**  
 INC.  
 Fort Worth, TEXAS

ENVIROFLEX Type LFNC-B  
 Liquidtight Flexible Nonmetallic Conduit

Drawn By: D. Gwinn    Date: 2/20/19    Ref. V06ADA1