


**Product Description**

Superior lubrication and durability in any weather or temperature. Perfect for use as a break-in lubricant for bearings or as a general purpose lubricant and corrosion inhibitor for tools, machinery and equipment.

**Product Specifications**

| | |
|---|---|
| **Applications** | Hinges, latches, overhead door tracks, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment. A break-in lubrication for bearings. |
| **Unit Package Description** | 16 Ounce Aerosol |
| **Brand** | CRC |
| **Generic Description 1** | White Lithium Aerosol Grease |
| **Net Fill** | 10 Wt Oz |
| **UPC Code** | 078254030807 |
| **Unit Dimensions** | 7.75H x 2.63W x 2.63D in |
| **Units Per Case** | 12 |
| **Case Dimensions** | 8.1H x 8.3W x 11.1D in |
| **Cases Per Pallet** | 133 |
| **Case Weight** | 11 lbs |
| **I 2 of 5 Code** | 30078254030808 |
| **Appearance** | Off-White Viscous Grease |
| **Odor** | Solvent |
| **Base Type** | Lithium Stearate |
| **Flashpoint** | <20°F |
| **CPSC Flammability Class** | Extremely Flammable |
| **Specific Gravity** | 0.6257 |
| **Plastic Safe** | Yes |
| **Film Type** | Grease |
| **Evaporation Rate** | Fast |
| **Working Temp** | 0 to 300°F |
| **Propellant** | Hydrocarbon |
| **NSF Category Code** | H2 |
| **NSF Registered** | Yes |
| **NSF Number** | 017410 |
| **Aerosol Flammability Level** | III |
| **360 Valve** | No |
| **DOT Proper Shipping Name** | Aerosols, Flammable, Limited Quantity |
| **VOC % (Federal)** | 85 |
| **VOC g/L (Federal)** | 531.8 |
| **VOC Lbs./Gal. (Federal)** | 4.43 |
| **VOC Category** | Not Regulated |
| **Removal (How To)** | Remove with Petroleum Distillates. |