CLAMPS "SNAP-ON" – STEEL

UL File No. E-184283
(Heavy Gauge)

Application:

- To support rigid conduit and IMC to mounting service



Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
410*	½″	100	500	5
411*	¾″	100	500	6
412*	1″	50	250	11
413*	1¼″	50	250	13
414	1½″	25	100	20
415	2″	25	25	22
206	2½″	25	25	64
207	3″	25	25	71
208	3½″	10	10	120
209	4″	10	10	130

* CSA Certified

CLAMPS – STEEL

(Light Gauge)



Cat. #	Conduit Sizes Rigid	Size of Strap Inside	Unit Quantity	Standard Package	Weight Lbs. Per 100
566	¼″	.540	500	500	2
567	⅜″	.675	200	1000	2

CABLE AND CONDUIT HANGERS – STEEL

With Bolts



Cat. #	Conduit Sizes Rigid	Conduit Size EMT	Unit Quantity	Standard Package	Weight Lbs. Per 100
0B	½″	⅜″ & ½″	100	100	6
1-B	¾″	¾″	100	100	6
2-B	1″	1″	100	100	8
2½-B	1¼″	—	100	100	10
3-B	1½″	1¼″	100	100	11
4-B	—	1½″	100	100	16
5-B	2″	2″	50	50	23
6-B	2½″	2½″	50	50	29
7-B	3″	3″	25	25	31
8-B	3½″	3½″	10	10	38
9-B	4″	4	10	10	38

BEAM CLAMPS/INSULATOR SUPPORTS – MALLEABLE IRON

UL File No. E-184283

- Standard finish: Zinc Plated



Cat. #	Base Size	Jaw Open	Max. Wt. Support	Tapped Holes	Unit Qty.	Std. Pkg.	Wt. Lbs./ 100
528*	¾″	⅝″	230	10 – 24	25	100	14
529*	¾″	⅝″	230	¼″ – 20	25	100	13
530	1″	¾″	230	10 – 24	25	100	23
531	1″	¾″	230	¼″ – 20	25	100	24
532	1½″	¾″	290	5⁄16″ – 18	50	50	47
533	2″	⅞″	330	⅜″ – 16	25	25	81
534	2½″	⅞″	800	½″ – 13	25	25	155

* Not UL listed

BEAM CLAMPS/INSULATOR SUPPORTS – STEEL



Cat. #	Base Size	Jaw Opening	Tapped Holes	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
529-S	¾″	⅝″	¼″ – 20	50	50	13

CONDUIT CLAMPS

Application:

Right Angle - to attach the conduit run at a 90° angle to a beam or structural member

Right Angle Type – Electrogalvanized – Iron



Cat. #	Trade Size	Load Rating Lbs	Standard Package	Weight Lbs. Per 100
RAC50HD	½″	30	50	37
RAC75HD	¾″	50	50	40
RAC100HD	1″	60	50	42
RAC125HD	1¼″	75	25	49
RAC150HD	1½″	80	25	54
RAC200HD	2″	100	25	71
RAC250HD	2½″	125	10	95
RAC300HD	3″	165	10	107
RAC350HD	3½″	200	10	120
RAC400HD	4″	330	10	131

Application:

Parallel Type - to attach the conduit run parallel to a beam or structural member

Parallel Type – Electrogalvanized – Iron




Cat. #	Trade Size	Load Rating Lbs	Standard Package	Weight Lbs. Per 100
PARC50HD	½″	30	50	50
PARC75HD	¾″	50	50	53
PARC100HD	1″	60	50	60
PARC125HD	1¼″	75	25	70
PARC150HD	1½″	80	25	82
PARC200HD	2″	100	25	132
PARC250HD	2½″	125	25	192
PARC300HD	3″	165	10	194
PARC350HD	3½″	200	10	216
PARC400HD	4″	330	10	232

CONDUIT CLAMPS

Applications:

Edge Type - to attach the conduit run at a 90° angle to a thin beam or structural member.

Edge Type – Electrogalvanized – Iron



Cat. #	Trade Size	Standard Package	Weight Lbs. Per 100
ETC50HD	½″	50	63
ETC75HD	¾″	50	69
ETC100HD	1″	50	82
ETC125HD	1¼″	25	95
ETC150HD	1½″	25	108
ETC200HD	2″	25	121
ETC250HD	2½″	25	153
ETC300HD	3″	10	214

Conduit Beam Clamp — J Type – Iron

UL File No. E-184283



Cat. #	Size	Max Weight Support	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
JCC1	½″	150	25	25	35
JCC2	¾″	150	25	25	43
JCC34	1″ & 1¼″	225	10	10	90
JCC56	1½″ & 2″	300	5	5	190
JCC78	2½″ & 3″	500	2	2	380
JCC910	3½″ & 4″	700	2	2	575

 Copyright© 2006 Cooper Crouse-Hinds