

MH-50X-D-FCAN

50W F-CAN METAL HALIDE



LAMP TYPE: 50W Metal Halide (M110)

INPUT VOLTAGE: Dual Tap (120/277)

CIRCUIT TYPE: HX-HPF


PRODUCT FEATURES

- ANSI Designation: M110
- Line Voltage: 120/277
- Regulation: 5%
- Frequency: 60 Hz
- Recommended Fuse (A): 3/2
- Circuit Type: HX-HPF
- Insulation Class: 105°C
- Capacitor: Integral
- Winding Materials: Cu/Cu
- Lamp Starter: N/A
- Agency Certification: UL, cUL Listed
- Maximum Distance to Lamp: 10 feet
- Warranty: 2 Years

ELECTRICAL SPECIFICATIONS


LINE VOLTAGE	POWER FACTOR	LINE CURRENT			INPUT POWER	OPEN CIRCUIT VOLTAGE	MINIMUM START TEMP	UL TEMP CODE
		OPERATING	OPEN CIRCUIT	STARTING				
120V	High	0.59A	1.31A	0.54A	67W	278V	-30°C/-22°F	A
277V	High	0.25A	0.55A	0.24A	65W	272V	-30°C/-22°F	A

PHYSICAL SPECIFICATIONS



LENGTH	11.80"
WIDTH	3.23"
HEIGHT	2.75"
MOUNTING	11.40"
NET WEIGHT	8.6 lbs
LEAD LENGTH	12-14"
CASE STYLE	D11

WIRING DIAGRAM



ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
MH-50X-D-FCAN	Individually Packaged	1	Quick Ship

CATALOG NUMBER BREAKDOWN

MH-50X-D-FCAN

