Product Specifications

1/4" x 3-1/4" Slotted Hex Washer Head Concrete Screw Anchor



Part number 14H314
Category number 4560
UPC 781002255284

Concrete Screws are tempered masonry screws designed for long lasting performance and superior holding strength. Due to their unique thread design, they are the ideal fastening solution for light to medium duty applications in concrete, brick, masonry block and wood base materials. They are manufactured with a gimlet point that taps it's own threads while drilling into the base material. Common applications for this fastener include the attachment of electrical boxes, light fixtures, and masonry base materials.

Physical Characteristics

Anchor Type	Concrete Screw
Head Type	Hex
Point Type	Gimlet
Thread Type	High-Low
Bit Size	#2
Hex Size	5/16"
Anchor Diameter	1/4"
Anchor Length	3-1/4"
Thread Length	3-1/4"
Material	Carbon Steel
Finish	Blue Xylan
Color	Blue

Packaging Details

Included	Carbide Tipped Drill
Standard Qty	100
Sleeve Qty	500
Master Qty	1000
Price Per	100
Package Length	5.75
Package Width	4.50
Package Height	3.00
Net Weight	0.03
Package Weight	3.00

Performance Data

Pre-Drill Size	3/16" x 5-1/2"

Applications
Poured Concrete
Prestressed Concrete
Cinder Block
Brick
Mortar

Special Features
Designed for Close To Edge Fastening, Strong Grip, Corrosion Resistance, Case Hardened, Can be Loosened for Adjustment or Removal

Cement Type	Various PSI

Certifications

RoHS Compliant	Yes