

Cable Hooks

- Supports Cat. 5/5e/6, fiber optic, innerduct and low voltage cabling requirements.
- Qwik-Latch™ cable retainers included with hooks.
- Static Load Capacity: 30 Lbs.
- Finsih: Pre-Galvanized

BCH12



Open



Closed



BCH21



BCH32



BCH64

UPC/Part Number	Catalog Number	Hook Size	Capacity Up To	Box Qty.
782051 28060	**BCH12**	3/4”	16 4-Pair UTP Cat 5e or 2-Strand Fiber Optic Cable or 10 CAT6	50
781011 04713	**BCH21**	1 5/16”	50 4-Pair UTP Cat 5e or 2-Strand Fiber Optic Cable or 32 CAT6	50
781011 04717	**BCH32**	2”	80 4-Pair UTP Cat 5e or 2-Strand Fiber Optic Cable or 50 CAT6	50
781011 04721	**BCH64**	4”	300 4-Pair UTP Cat 5e or 2-Strand Fiber Optic Cable or 185 CAT6	25

Patent #5961081

For special finish colors see page 151

(See pages 234-235 for technical data.)

Read safety/installation instruction sheets in packages before use.



Painted Cable Hooks

- Powder coated cable hooks are available in a range of colors to help meet your cable identification requirements.
- Standard riveted assemblies are available with painted cable hooks.
- Part numbers can be made by adding the paint color suffix after the cable hook part number.
- Minimum order quantity 500 pieces.
- Standard lead time is 5-10 working days.


Bright White - BW	Green - GR
Brown - BR	Orange - OR
Computer White - CW	Regal Red - RR
Equipment Blue - BL	Safety Yellow - YL
Flat Black - FB	Telcom Gray - TG


Part # Example:
Painted Cable Hook Part Number - BCH32BW
Painted Cable Hook Assembly - BCH32BW-U24

Replacement Cable Retainers

- Exclusive Qwik-Latch™ retainers are included on all cable hook purchases.
- Provides secure containment of cables and offers quick open/close feature to add or remove cables.
- Finish: Pre-galvanized







Retainer in open position



Push retainer down to lock

UPC/Part Number	Catalog Number	Cable Retainer For Hook Size	Box Qty.
781011 04847	**BCHR21**	$1\frac{5}{16}$”	50
781011 04848	**BCHR32**	2”	50
781011 04849	**BCHR64**	4”	50

Patent #5961081

Read safety/installation instruction sheets in packages before use.