

Cable-In/Cable-Out,
1/2-Inch WideQCF Breaker Catalog Numbers ^{1 2 3}

Continuous Ampere Rating at 40°C	Single-Pole 120/240 Vac Catalog Number	Two-Pole 120/240 Vac Catalog Number	Two-Pole 240 Vac ⁴ Catalog Number	Three-Pole Catalog Number
QCF Breaker 10 kAIC Interrupting Ratings				
10	QCF1010	QCF2010	—	—
	QCF1010T	QCF2010T	—	—
15	QCF1015 ⁵	QCF2015	QCF2015H	QCF3015H
	QCF1015T ⁵	QCF2015T	QCF2015HT	QCF3015HT
20	QCF1020 ⁵	QCF2020	QCF2020H	QCF3020H
	QCF1020T ⁵	QCF2020T	QCF2020HT	QCF3020HT
25	QCF1025	QCF2025	QCF2025H	QCF3025H
	QCF1025T	QCF2025T	QCF2025HT	QCF3025HT
30	QCF1030	QCF2030	QCF2030H	QCF3030H
	QCF1030T	QCF2030T	QCF2030HT	QCF3030HT
35	QCF1035	QCF2035	—	—
40	QCF1040	QCF2040	—	—
45	QCF1045	QCF2045	—	—
50	QCF1050	QCF2050	—	—
55	QCF1055	QCF2055	—	—
60 ⁶	QCF1060	QCF2060	—	—
QCF Breaker 22 kAIC Interrupting Ratings				
15	QCFH1015 ⁵	QCFH2015	—	—
	QCFH1015T ⁵	QCFH2015T	—	—
20	QCFH1020 ⁵	QCFH2020	—	—
	QCFH1020T ⁵	QCFH2020T	—	—

Notes

- ¹ Standard breaker terminals are box type lugs.
- ² Breakers with **T** Catalog Number Suffix are suitable for line and load side ring terminal connection (#10–32 plus/minus terminal screw provided).
- ³ Breakers with Shunt Trip Attachment (extra pole required on breaker right-hand side) are available. Contact the Customer Support Center.
- ⁴ Breakers with **H** Catalog Suffix have 240 Vac construction.
- ⁵ All 15 and 20A single-pole breakers are SWD (Switching Duty) rated for fluorescent lighting applications.
- ⁶ 60/75°C Cu/Al wire on all ratings except 60A, which requires Cu only conductor.