

1MM and 3MM Metering Circuit Breakers



CV2200

Contents

Description

Page

Systems for Residential and Commercial Applications	V1-T5-88
Meter Packs	V1-T5-90
Type CCV 120/240V Tenant Main Circuit Breaker	V1-T5-95
Type CV 120/240V Tenant Main Circuit Breaker	V1-T5-96
Meter Packs—1MP, 1MM and 3MM Main Tenant Circuit Breakers	V1-T5-98
Main Service Modules	V1-T5-101
Surge Metering	V1-T5-115
Residential Meter Stacks	V1-T5-116
1MP, 1MM and 3MM Main Tenant Circuit Breakers	V1-T5-126
Phase Balanced Stack	V1-T5-127
Commercial Meter Stack Modules	V1-T5-127
35MM, 37MM, 35SS and 37SS Main Tenant Circuit Breakers	V1-T5-134

1MP, 1MM and 3MM Main Tenant Circuit Breakers

Product Description

Specific main tenant circuit breakers that are to be used in meter packs (1MP), residential meter stacks (1MM) and three-phase in single-phase out meter stacks (3MM).

Product Selection

Description	Number of Poles	Main Tenant Circuit Breaker Ampere Rating	10 kAIC Catalog Number ¹	22 kAIC Catalog Number	25 kAIC Catalog Number ^{1 2 3 4}	42 kAIC Catalog Number ^{2 3 4}	65 kAIC Catalog Number ^{2 3 4}	100 kAIC Catalog Number ^{2 3 4}
Plug-On Type								
Plug-on type circuit breakers used with 1MP, 1MM, and 3MM 125A modular metering stacks	2	60	BR260	BRH260	—	BRHH260	—	—
	2	70	BR270	BRH270	—	BRHH270	—	—
	2	80	BR280	BRH280	—	BRHH280	—	—
	2	90	BR290	BRH290	—	BRHH290	—	—
	2	100	BR2100	BRH2100	—	BRHH2100	—	—
	2	110	BR2110	BRH2110	—	BRHH2110	—	—
	2	125	BR2125	BRH2125	—	BRHH2125	—	—
Bolt-On Type								
Bolt-on type circuit breakers used with 1MP, 1MM, and 3MM 200A modular metering stacks	2	60	—	—	CVS2060XMM	CVS2060XMM	CV2060XMM	CVH2060XMM
	2	70	—	—	CVS2070XMM	CVS2070XMM	CV2070XMM	CVH2070XMM
	2	80	—	—	CVS2080XMM	CVS2080XMM	CV2080XMM	CVH2080XMM
	2	90	—	—	CVS2090XMM	CVS2090XMM	CV2090XMM	CVH2090XMM
	2	100	CCV2100X	—	CCVH2100X	CVS2100XMM	CV2100XMM	CVH2100XMM
	2	125	CCV2125X	—	CCVH2125X	CVS2125XMM	CV2125XMM	CVH2125XMM
	2	150	CCV2150X	—	CCVH2150X	CVS2150XMM	CV2150XMM	CVH2150XMM
	2	175	CCV2175X	—	CCVH2175X	CVS2175XMM	CV2175XMM	CVH2175XMM
	2	200	CCV2200X	—	CCVH2200X	CVS2200XMM	CV2200XMM	CVH2200XMM

Notes

¹ #2–300 kcmil wire size range for CCV and CCVH tenant main circuit breakers.

² “MM” suffix indicates mounting hardware kit is included as standard with tenant main breaker.

³ 1MMCBK replacement mounting hardware kit. One kit is needed per breaker. Mounting hardware kit ships standard with breaker “MM” suffix offering.

⁴ #6–4/0 kcmil wire size range for CVS, CV and CVH tenant main circuit breakers. If #2–300 kcmil is needed, order 2TA225CVK. One kit needed per breaker.