

Features

2

Base Mounting Hardware

Metric base mounting hardware is included with each breaker. English mounting hardware is available for field installation only.

Base Mounting Hardware

Frame	Catalog Number	
	English	Metric
GP ^①	—	—
FP	BMH1	BMH1M
KP	BMH3	BMH3M
LP	BMH4	BMH4M
MP	BMH5	BMH5M

Line and Load Terminals

Both line and load terminals are included with GP-Frame Definite Purpose breakers.

Line and Load Termination

Breaker	Termination Type	Awg Wire Range	Metric Wire Range (mm)	Wire Type	Bolt Size English	Bolt Size Metric	Torque Lb-In	Torque Nm	Catalog Number
GP	Wire	#14–1/0	2.5–50	Cu only	—	—	45	5.1	Included

Options

Optional Line and Load Terminals

Compression terminals with hardware are available for a wide range of conductors. Field installation only.

Optional Line and Load Terminals

Breaker	Maximum Amperes	Awg Wire Range	Wire Type	Catalog Number	Catalog Number with Control Wire Termination
FP	100	#14–#10	Cu/Al	3T100FB ^②	—
	100	#8	Cu/Al	3T100FB ^②	—
	100	#6–#4	Cu/Al	3T100FB ^②	—
	100	#3–4/0	Cu/Al	3T100FB ^②	—
	200	#3–4/0	Cu only	3T150FB ^②	—
	225	#4–4/0	Cu/Al	3TA225FB ^②	—
	225	#6–300	Cu/Al	3TA225FDK ^②	—
KP	400	250–500 (1)	Cu/Al	TA350K	—
	400	3/0–250 (2)	Cu/Al	3TA400K ^②	3TA400KCW
LP	500	250–350 (2)	Cu/Al	TA602LD	TA602LDCW
	600	400–500 (2)	Cu/Al	3TA603LDK ^②	3TA603LDCW
MP	800	3/0–400 (3)	Cu/Al	TA800MA2	TA800MA2CWT
	800	500–750 (2)	Cu/Al	TA801MA	TA801MACWT

Notes

① Base mounting hardware, is included with GP-Frame breakers. A separate catalog number is not required.

② Package of three terminals.