

Specifications

Photo is representative

Eaton PDG33M0400TFAN

Eaton Power Defense Globally Rated, Frame 3, Three Pole, 400A, 65kA/480V, T-M (Fxd-Adj) TU, No Terminals

General specifications

PRODUCT NAME	Eaton Power Defense molded case circuit breaker
CATALOG NUMBER	PDG33M0400TFAN
UPC	786679270318
PRODUCT LENGTH/DEPTH	4.29 in
PRODUCT HEIGHT	7 in
PRODUCT WIDTH	5.46 in
PRODUCT WEIGHT	11.95 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	CCC Marked UL 489 IEC 60947-2 CSA



Powering Business Worldwide

Delivery program

AMPERAGE RATING 400 A

CIRCUIT BREAKER FRAME TYPE Complete breaker

FRAME 3

NUMBER OF POLES Three-pole

Technical data - Electrical

VOLTAGE RATING 600 Vac

Technical information

INTERRUPT RATING 65 kAIC at 480 Vac

INTERRUPT RATING RANGE 22 kAIC Icu @250 Vdc
100 kAIC @240V (UL)

General information

CIRCUIT BREAKER TYPE PD3 Global

CLASS Class A

TRIP TYPE T297

Technical data - Mechanical - Terminals

TERMINALS No Terminals

Resources

3D CAD DRAWING PACKAGE [Eaton Power Defense MCCB PDG33M0400TFAN 3D drawing](#)

APPLICATION NOTES [Consulting application guide - molded case circuit breakers](#)

[StrandAble terminals product aid](#)

[Power Defense technical selling booklet](#)

BROCHURES

[Power Defense molded case circuit breaker selection poster](#)

[Power Defense brochure](#)

CATALOGS [Circuit Protection, Molded Case Circuit Breakers, Volume 4, Tab 2](#)

[PDG3 CSA certification 100-400a](#)

[PDG3 UL authorization 250-600a TMTU](#)

[PDG3 CSA certification 250-600a](#)

CERTIFICATION REPORTS [PDG3 UL authorization 100-400a](#)

[EU Declaration of Conformity - Power Defense molded case circuit breakers](#)

[PDG3B 450A-600A CB report](#)