

Product Selection

Types KD, HKD and KDC Thermal-Magnetic Circuit Breakers with Interchangeable Trip Units

2

Maximum Continuous Ampere Rating at 40°C	Standard Interrupting Capacity 600 Vac Rated 35 kAIC at 480 Vac Factory Assembled Circuit Consisting of Frame, Trip Unit and Terminals ¹ Catalog Number	High Interrupting Capacity 600 Vac Rated 65 kAIC at 480 Vac Factory Assembled Circuit Consisting of Frame, Trip Unit and Terminals ¹ Catalog Number	Ultra High Interrupting Capacity Current Limiting 600 Vac Rated 100 kAIC at 480 Vac Factory Assembled Circuit Consisting of Frame, Trip Unit and Terminals ¹ Catalog Number	Thermal-Magnetic Trip Unit Only ¹ For Use with Standard or High or Ultra High Interrupting Frames Catalog Number	Standard Terminals Only See Page V4-T2-173 for Optional Terminals Catalog Number
Two-Pole					
100	KD2100	HKD2100	KDC2100	KT2100T	TA300K ²
125	KD2125	HKD2125	KDC2125	KT2125T	TA300K ²
150	KD2150	HKD2150	KDC2150	KT2150T	TA300K ²
175	KD2175	HKD2175	KDC2175	KT2175T	TA300K ²
200	KD2200	HKD2200	KDC2200	KT2200T	TA300K ²
225	KD2225	HKD2225	KDC2225	KT2225T	TA300K ²
250	KD2250	HKD2250	KDC2250	KT2250T	TA350K ²
300	KD2300	HKD2300	KDC2300	KT2300T	TA350K ²
350	KD2350	HKD2350	KDC2350	KT2350T	TA350K ²
400	KD2400	HKD2400	KDC2400	KT2400T	2TA400K ³
Three-Pole					
100	KD3100	HKD3100	KDC3100	KT3100T	TA300K ²
125	KD3125	HKD3125	KDC3125	KT3125T	TA300K ²
150	KD3150	HKD3150	KDC3150	KT3150T	TA300K ²
175	KD3175	HKD3175	KDC3175	KT3175T	TA300K ²
200	KD3200	HKD3200	KDC3200	KT3200T	TA300K ²
225	KD3225	HKD3225	KDC3225	KT3225T	TA300K ²
250	KD3250	HKD3250	KDC3250	KT3250T	TA350K ²
300	KD3300	HKD3300	KDC3300	KT3300T	TA350K ²
350	KD3350	HKD3350	KDC3350	KT3350T	TA350K ²
400	KD3400	HKD3400	KDC3400	KT3400T	3TA400K ³
Four-Pole					
100	KD4100	HKD4100	KDC4100	KT3100T	TA300K ²
125	KD4125	HKD4125	KDC4125	KT3125T	TA300K ²
175	KD4175	HKD4175	KDC4175	KT3175T	TA300K ²
200	KD4200	HKD4200	KDC4200	KT3200T	TA300K ²
225	KD4225	HKD4225	KDC4225	KT3225T	TA300K ²
250	KD4250	HKD4250	KDC4250	KT3250T	TA350K ²
300	KD4300	HKD4300	KDC4300	KT3300T	TA350K ²
350	KD4350	HKD4350	KDC4350	KT3350T	TA350K ²
400	KD4400	HKD4400	KDC4400	KT3400T	4TA400K ³

Notes

¹ Magnetic trip adjustable 5–10 times continuous ampere rating.² Individually packed.³ 2TA400K, 3TA400K and 4TA400K terminal kits contain one terminal for each pole and one terminal cover.