


Non-CTL Plug-On Replacement—Circuit Breakers, Type BRD—10 kAIC, 120/240 Vac

BR2020

Class Non-CTL, 1-Inch (25.4 mm) per Pole 10 kAIC—Breakers Do Not Have Rejection Tab Feature




Type BR Duplex



Single-Pole Requires One
1-Inch (25.4 mm) Space
10 per Shelf Carton

Ampere Rating	Catalog Number	Wire Size Range Cu/Al 65°C or 75°C
15–15	BR1515	#14–4
15–20	BR1520	#14–4
20–15	BR2015	#14–4
20–20	BR2020	#14–4
30–30	BR3030	#14–4
30–50	BR3050	#14–4


Type Brand BRD Quadplex Independent Trip



Two-Pole Requires Two
1-Inch (25.4 mm) Spaces
5 per Shelf Carton

120/240 Vac Ampere Rating Outer Two-Pole Independent Trip	120/240 Vac Ampere Rating Center Two-Pole Independent Trip
15	15
20	20
30	30
20	30
30	40
30	50


Type BRD Quadplex Common Trip Center and Outer Poles



Two-Pole Requires Two
1-Inch (25.4 mm) Spaces
5 per Shelf Carton

120/240 Vac Ampere Rating Outer Two-Pole Common Trip	120/240 Vac Ampere Rating Center Two-Pole Common Trip	Catalog Number
15	15	BRDC215215
30	30	BRDC230230
30	40	BRDC230240
30	50	BRDC230250
—	—	—
—	—	—

CTL and Non-CTL Breakers



Note

Type BD Duplex, BQ and BQC Quadplex circuit breakers can be installed in Circuit Limiting (CTL) listed BR loadcenters. Type BR twin breakers can be installed in Non-CTL BR loadcenters.