




RIGID BODIES AND ASSEMBLIES

LL Assembly

C13



Catalog #: RLL250

APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.

PRODUCT FEATURES

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

UL LISTED

File E331564

NEMA

NEMA 3R rated

NEC

2014 NEC® compliant

GENERAL PRODUCT INFORMATION

Trade Size: 2-1/2 in.

DRAWING DIMENSIONS

Dimension A: 12.83 in.
Dimension B: 5.89 in.
Dimension C: 3.98 in.
Dimension D: 4.49 in.
Dimension E: 11.250 in.
Dimension F: Tapped holes #5/16UNC-2B
Dimension G: 2-1/2-8NPT
Dimension H: 2.459 in.

PRODUCT MEASUREMENTS

Cubic Inches (cm3): 157.4 (2579.3)

PACKAGING

Package Type: Carton
Ship Carton Qty.: 1
Product UPC-A Labeled: Yes
Weight (Lbs. Per/C): 442
Ship Carton Length (in.): 11.02
Ship Carton Width (in.): 5.59
Ship Carton Height (in.): 7.48
Ctn Weight (Lbs.): 4.42
UPC Number: 092326213288
I2of5: 30092326213289