

FLEX • AC • MC FITTINGS

**4501**

45° CONNECTORS

For aluminum and steel Flex • AC • MC cable.

Zinc die-cast.

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	K.O. SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
4501	04501	3/8	1/2	50	500	.382	1.132	1.588	.445- .612	.620
4502	04502	1/2	1/2	25	250	.382	1.150	1.775	.620- .895	.635

Refer to the [chart](#) for a list of cable types.

**4501ST**

45° SNAP-TITE® CONNECTORS

With spring steel clip.

For aluminum and steel Flex • AC • MC cable.

Zinc die-cast.

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	K.O. SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
4501ST	06002	3/8	1/2	50	500	.382	1.132	1.588	.445- .612	.620
4502ST	06004	1/2	1/2	25	250	.382	1.150	1.775	.620- .895	.635

Refer to the [chart](#) for a list of cable types.

Patented.

SNAP-TITE® products have been tested and listed by UL
in accordance with UL's ground fault requirements.

For additional information [click here](#).

**850**

90° CONNECTORS

For aluminum and steel Flex • AC • MC cable.

Zinc die-cast.

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	K.O. SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
850	00850	3/8	1/2	50	500	1.370	.340	1.800	.440- .750
851	00851	1/2	1/2	25	250	1.780	.410	2.140	.635- 1.085
852	00852	3/4	3/4	15	150	2.065	.500	2.380	.830- 1.380
853	00853	1	1	10	50	2.560	.500	2.080	1.330- 1.570
854	00854	1-1/4	1-1/4	5	25	2.812	.500	3.080	1.625- 1.940
855	00855	1-1/2	1-1/2	1	10	4.875	.750	6.050	1.400- 2.400
856	00856	2	2	1	10	4.875	.750	6.050	1.400- 2.400
† 857	00857	2-1/2	2-1/2	1	1	6.125	.875	7.187	2.600- 3.100
† 858	00858	3	3	1	1	6.700	1.031	7.875	3.100- 3.640
† 859	00859	3-1/2	3-1/2	1	1	7.500	1.031	9.400	3.380-

										4.220	E1
† 8510	08510	4	4	1	1	8.700	1.031	10.200	3.730-	4.550	

Refer the [chart](#) for a list of cable types.

†Malleable.

[Products Index](#)

[Table of Contents](#)

[Next](#)