

B52**LIQUIDTIGHT CONDUIT AND CORD CONNECTORS****STEEL/MALLEABLE IRON - STRAIGHT CONNECTORS****RACO COMMERCIAL FITTINGS****Applications**

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO® liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable — RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- **Bodies**
3/8" to 1" Steel
1-1/4" to 4" Malleable Iron
- **Nuts**
3/8" to 1" Steel
1-1/4" to 4" Malleable Iron

Compliances

-  — Standard 514B
-  — C22.2 #18



Straight - Insulated
Steel/Malleable Iron



Straight - Uninsulated
Steel/Malleable Iron


ORDERING INFORMATION - DIMENSIONS**STRAIGHT - INSULATED AND UNINSULATED - STEEL/MALLEABLE IRON**

INSULATED IRON CATALOG NUMBER	UNINSULATED IRON CATALOG NUMBER	TRADE SIZE	UNIT CTN. QTY.	SHIP CTN. QTY.	UPC BAR CODE
3511RAC*	—	3/8"	25	100	—
—	3401*	3/8"	50	200	—
—	3401-8*	3/8"	1	15	
3512RAC	3402	1/2"	50	200	—
3512-8	3402-8	1/2"	1	15	
3513RAC	3403	3/4"	25	100	—
3513-8	3403-8	3/4"	1	10	
3514RAC	3404	1"	—	10	—
3514-8	3404-8	1"	1	5	
3515RAC	3405	1-1/4"	—	10	—
3516	3406	1-1/2"	—	5	—
3518	3408	2"	—	5	—
3520	3410	2-1/2"	—	1	—
3522	3412	3"	—	1	—
3524	3414	3-1/2"	—	1	—
3526	3416	4"	—	1	—

*1/2" Trade size hub

DIMENSIONS

TRADE SIZE	A	B	THD. SPEC.	C
3/8"	1-1/16"	1/2"	1/2"-14 NPT	1-29/64"
1/2"	1-3/16"	1/2"	1/2"-14 NPT	1-15/32"
3/4"	1-13/32"	9/16"	3/4"-14 NPT	1-31/64"
1"	1-45/64"	19/32"	1"-11-1/2 NPT	1-51/64"
1-1/4"	2-3/16"	43/64"	1-1/4"-11-1/2 NPT	1-7/8"
1-1/2"	2-13/32"	47/64"	1-1/2"-11-1/2 NPT	2-11/64"
2"	3-1/32"	21/32"	2"-11-1/2 NPT	2-9/32"
2-1/2"	3-5/8"	1"	2-1/2"- 8 NPT	3-5/16"
3"	3-3/8"	1-3/64"	3"- 8 NPT	3-1/2"
3-1/2"	3-31/32"	1-1/8"	3-1/2"- 8 NPT	3-5/8"
4"	5-35/64"	1-5/32"	4"- 8 NPT	3-5/8"



A = Nut Flats
B = Thread length and thread spec.
C = Overall Length