

BELL • CHALMIT • HAWKE INTERNATIONAL • KILLARK • RACO

HEPnet

RACO

Search RACO

GO

Home | Products | Company | Support | Contact

April 21, 2008

Products

Index
Featured Products
Cross Reference
UPC Search

Product Datasheet

Catalog Home

Home Page

Search

3416 -- Straight Liquidtight Connector 4" Trade Size

Product Specifications	
Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Steel / Malleable Iron - Straight Connectors
Sub Class	Uninsulated
Trade Size	4"
Standard Packaging	Carton
Ship Carton Length	5.75
Ship Carton Width	5.75
Ship Carton Height	4.5
WT. PER HU.	560
Dimension A	5-35/64"
Dimension B	1-5/32"
Thread Spec. B	4-8 NPT
Dimension C	3-5/8"
Unit Carton Quantity	1
Ship Carton Quantity	1
UPC Number	05016903416

Applications


- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO® liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

Compliances

UL CSA



[Login](#) | [Privacy](#) | [Site Map](#)

© 2003 RACO - a hubbell company. All right reserved.