

Steel EMT Set-Screw Connectors and Couplings

4000S Series Connectors

Features

- Heavy steel walls.
- Concretetight when taped.
- Pre-set/Pre-staked set screws.
- Male hub threads NPS.
- Available with insulated throat.
- Three-way combination screws.
- Insulated throat connector rated 90°C.

Standard Materials

- Steel.

Standard Finish


- Zinc Plated.

Third Party Certification

- UL Listed: E-14815 (1/2" to 2")
- UL Listed: E-14816 (2-1/2" to 4")

Applicable Third Party Standards

- UL 514B
- CSA Standard C22.2 No. 18
- NEMA FB-1
- Federal Spec. W-F-408E



Type 4050S — Type 4100S



Type 4125S — Type 4400S

Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches Body Length	Max Dia.	Thread Length	Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
1/2	4050S	4050ST	1-1/32	27/32	7/16	10	25	250
3/4	4075S	4075ST	1-3/32	1-5/64	7/16	15	20	200
1	4100S	4100ST	1-3/16	1-5/16	7/16	23	20	100
1-1/4	4125S	4125ST	1-3/4	1-11/16	9/16	42	10	40
1-1/2	4150S	4150ST	1-15/16	1-15/16	9/16	53	10	40
2	4200S	4200ST	2-3/16	2-3/8	5/8	75	5	20
2-1/2	4250S	4250ST	2-3/8	3-1/8	7/8	130	—	10
3	4300S	4300ST	2-7/8	3-3/4	7/8	230	—	5
3-1/2	4350S	4350ST	3	4-1/4	1	250	—	5
4	4400S	4400ST	3-3/16	4-3/4	1	250	—	5

5000S Series Couplings

Features

- Heavy steel walls.
- Concretetight when taped.
- Pre-set/Pre-staked set screws.
- Three-way combination screws.

Standard Materials

- Steel.

Standard Finish


- Zinc Plated.

Third Party Certification


- UL Listed: E-14815 (1/2" to 2")
- UL Listed: E-14816 (2-1/2" to 4")

Applicable Third Party Standards

- UL 514B
- CSA Standard C22.2 No. 18
- NEMA FB-1
- Federal Spec. W-F-408E



Type 5050S — Type 5100S



Type 5125S — Type 5400S

Trade Size (Inches)	Catalog Number	Dimension in Inches Body Length	Max. Dia.	Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
1/2	5050S	1-3/4	27/32	10	25	250
3/4	5075S	2-1/8	1-5/64	16	20	200
1	5100S	2-1/2	1-5/16	25	20	100
1-1/4	5125S	3-1/4	1-11/16	45	10	40
1-1/2	5150S	3-3/4	1-15/16	60	10	40
2	5200S	4	2-3/8	82	5	20
2-1/2	5250S	4-1/4	3-1/8	166	—	10
3	5300S	4-1/2	3-3/4	213	—	5
3-1/2	5350S	4-3/4	4-1/4	260	—	5
4	5400S	5	4-3/4	300	—	5

All dimensions are approximate and subject to change.