

ETP Raintight Steel EMT Compression Connectors

Raintight Gland Compression Connectors: 7000NSR Series

Application

- To ground and secure EMT raceway to boxes and enclosures in wet locations.

Features

- UL Listed Raintight.
- No disassembly required.
- Male hub threads NPS.
- Available with and without insulated throat.
- Concretetight.

Standard Materials

- Body and nut: steel
- Knockout sealing ring: EPDM rubber

Standard Finish

- Body and nut: zinc electroplate

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- UL Listed Raintight



7100NSR



7100NSRT

Trade Size (Inches)	Dimensions in Millimeters (Inches)			Weight per 100 pcs kgs (lbs)	Catalog Number	
	Body Length	Maximum Diameter	Thread Length		Without Insulated Throat	Insulated Throat
1/2	36.6 (1.44)	27.9 (1.10)	8.6 (0.34)	4.5 (10)	7050NSR	7050NSRT
3/4	38.1 (1.50)	34.5 (1.36)	8.6 (0.34)	6.8 (15)	7075NSR	7075NSRT
1	44.5 (1.75)	34.5 (1.36)	9.9 (0.39)	10.0 (22)	7100NSR	7100NSRT
1-1/4	50.8 (2.00)	52.6 (2.07)	10.2 (0.40)	16.3 (36)	7125NSR	7125NSRT
1-1/2	50.8 (2.00)	58.7 (2.31)	10.2 (0.40)	18.1 (40)	7150NSR	7150NSRT
2	58.9 (2.32)	70.9 (2.79)	10.4 (0.41)	24.5 (54)	7200NSR	7200NSRT
2-1/2	91.9 (3.62)	92.2 (3.63)	16.5 (0.65)	68.0 (150)	7250NSR	7250NSRT
3	95.3 (3.75)	109.0 (4.29)	16.5 (0.65)	83.9 (185)	7300NSR	7300NSRT
3-1/2	97.8 (3.85)	121.9 (4.80)	18.3 (0.72)	97.5 (215)	7350NSR	7350NSRT
4	99.1 (3.90)	133.9 (5.27)	18.3 (0.72)	108.0 (238)	7400NSR	7400NSRT