



ARCY-Line: 2' & 4' LED Wrap

Extra Wide Width


CCT Tunable via ENVISIONLS



2FT-3P25		4FT-3P50	
WATT	LUMENS	WATT	LUMENS
15	1,850	30	3,900
20	2,600	40	5,200
25	3,250	50	6,500



Devices



CCT-Select / Dimming



Wall Switch
S-WS-DIM-TUN-UNV-BT

Series	Size	Power	CCT	Emergency
LED-WRP-ARC -			- TUN -	
	10ix2FT	2FT-25W	30-65K	(Blank)
	9.8" wide	3,250LM	Tunable	No Sensor
	x 24" long	4FT-50W		EMB
	10ix4FT	5,520LM		Emergency Backup
	9.8" wide			
	14ix2FT			
	14" wide			
	x 24" long			
	14ix4FT			
	14" wide			
	x 47" long			

Project: _____ Part #: _____
Type: _____

Wraps



Detail Specifications:

- Finish: White
- IP Rating: Damp Location (IP44)
- Beam Angle: 130°
- Chip: SMD 2835, R9 >50, CRI >80
- 5-CCT: 30/35/40/50/65k
- Operating Temperature: -40° - 122° F
- Lens: Frosted Lens
- Average life (L70) of 50,000 hours

Applications:

- Stairwell & Hallways
- Utility & Storage
- Garage Structures
- Office and Meeting Rooms
- Shop Lighting
- Residential, Commercial and Industrial

Product Information:

- Aluminum housing finished with corrosion free power coat
- Extra wide length, ideal for use in retrofit scenarios
 - 10i: 9.8" wide
 - 14i: 14" wide
- Select-n-Switch Technology: 5-CCT + 3-Power Selectable
- ½" Knockout on both ends of the fixture
- Control Options:
 - Standard Sensors
 - SILVAIR Bluetooth Mesh
 - ENVISIONLS Bluetooth
 - [Click Here](#) for More Information

Driver Options:

- UNV: 120-277V 0-10V Dimmable
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz
- Flicker Free

Mounting & Installation:

- Surface mount into 30 or 40 j-box
- Optional 10' & 20' suspension kit available

Certifications:


- ETL Listed for USA and CA
- DLC Standard Listed
 - 10i-2FT: S-C5CHG6
 - 10i-4FT: S-6G51MK
 - 14i-2FT: S-3WR25L
 - 14i-4FT: S-D3FSSD
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

Optional Accessories (Order Separately)


Accessories	Wall Dimmer & Tuning
SK-10FT-Y-LC-PD 10' Y-Shape, Loop Top, Paddle Bottom (Adjustable Length)	S-WS-DIM-TUN-UNV-BT Dimmer + Tuning Slider
SK-20FT-Y-LC-PD 20' Y-Shape, Loop Top, Paddle Bottom (Adjustable Length)	

Specs and model numbers are subject to change with or without notice.

FEATURES



DIMENSIONS



ARCY-Line: 2' & 4' LED Wrap

Extra Wide Width

CCT Tunable via ENVISIONLS

ACCESSORIES



SK-10FT-Y-LC-PD
SK-20FT-Y-LC-PD



S-WS-DIM-TUN-UNV-BT

Model	Voltage	Watts	Lumens	Color	CRI
LED-WRP-ARC-10ix2FT-25W-TUN	120-277V	25w	3,250	30-65K Tunable	>80
LED-WRP-ARC-10ix4FT-50W-TUN	120-277V	50w	6,500	30-65K Tunable	>80
LED-WRP-ARC-14ix2FT-25W-TUN	120-277V	25w	3,250	30-65K Tunable	>80
LED-WRP-ARC-14ix4FT-50W-TUN	120-277V	50w	6,500	30-65K Tunable	>80

SUSPENSION KIT

Model	Description
SK-10FT-Y-LC-PD	Suspension Kit: 10' Y-Shape, Loop Top, Paddle Bottom (Adjustable Length)
SK-20FT-Y-LC-PD	Suspension Kit: 20' Y-Shape, Loop Top, Paddle Bottom (Adjustable Length)

WALL DIMMER

Model	Description
S-WS-DIM-TUN-UNV-BT	Dimmer + Tuning Slider

EnVisionLED™ Control Options

EnVision LED offers 3 control systems compatible with our LED Fixtures for projects of all sizes and budgets.

	Basic Controls	EnVisionLS 	EnVisionLED x SILVAIR 
Description	Standard Plug In Sensors	Basic Bluetooth Wireless Control	Advanced Bluetooth Wireless Control
Recommended Quantity (but not limited to)	N/A	>40-50 Nodes	>50 Nodes
Maximum Zone Quantity	N/A	100	3,000
Commissioning Tool	Remote Only	  ENVISIONLS App 	  SILVAIR App 
Commissioning Process	Individually Set via Remote	Wireless Must be done on site	Wireless- Initial linking must be done on site. Commissioning can be done via desktop remotely.
Floor Plan Upload	N/A	N/A	Yes Add a floor plan and mark luminaires & zones via desktop
Gateway	N/A	N/A	Required only for energy monitoring, advanced scheduling, automated demand response.
Individual Luminaire Control	Yes	Yes	Yes
Luminaire Grouping Zoning	N/A	Yes	Yes
High End Power Low End Power	Yes but limited (View Remote)	Yes	Yes
Cost	\$	\$\$	\$\$\$
DLC NLC Listed	N/A	Yes	Yes
Energy Monitoring & Data Reporting	N/A	N/A	Monitor energy usage per individual zone & retrofit cost savings calculation + detailed reporting



Compatible Products:

EnVision offers a variety of nodes, sensors, & gateways that are controlled via remote, ENVISIONLS Bluetooth Mesh & SILVAIR Bluetooth Mesh on all of our 0-10V dimmable fixtures.



Individual Fixture Controls: PIR Sensor, Bi-Level Dimming, Daylight

Basic Note: -1 • ENVISIONLS Models Note: -BT • SILVAIR Models Note: -SL

	MODEL #	DESIGN	RECOMMENDED FIXTURE	FEATURES
	S-TWC-PIR-1 S-TWC-PIR-BT S-TWC-PIR-SL	Twist-C Control Sensor	Sensor Ready Fixtures: Area Lights, Canopies, Flood Lights, High Bays	All models are equipped with PIR occupancy sensing, high & low end bi-level dimming, & daylight sensing.
	S-TWC-90 + S-TWC-PIR-1 S-TWC-90 + S-TWC-PIR-BT S-TWC-90 + S-TWC-PIR-SL	Twist-C Control Sensor + 90 Degree Arm	Cylinders, Strips, Wall Packs	
	S-AUD-PIR-1 S-AUD-PIR-BT S-AUD-PIR-SL	2.5m Audio Jack	Panels & Troffers	
	S-SN-PIR-1 S-SN-PIR-BT S-SN-PIR-SL	Snap In Sensor	Troffers & Wraps	

Group Controls ENVISIONLS Models Note : -BT • SILVAIR Models Note: -SL

	MODEL #	DESIGN	VOLTAGE	FEATURES	RECOMMENDED FEATURES
	S-CM-PIR-LV-BT S-CM-PIR-LV-SL	Ceiling Mounted PIR Sensor	12-24V	PIR Sensor, Bi-Level Dimming, Daylight, 360° detection, 12' Max Mounting Height	Connects to 0-10V dimmable fixtures
	S-WM-PIR-CUNV-BT S-WM-PIR-CUNV-SL	Wall Mounted PIR Occupancy Sensor, Bi-Level Dimming, Daylight	120-277V	On/Off PIR occupancy sensor, 180° detection, 30' detection @ 4' Mounting Height	Connects to LED fixtures
	S-WS-120V-USB-SL		120V	Dimming Wall Socket, Two Sockets	Floor Lamps, Other Lamps

Gateway (Silvair Only) 4.5–5.5 V DC, 2A Power over Ethernet 36–57 V DC

	MODEL #	DESIGN	VOLTAGE	FEATURES	RECOMMENDED FEATURES
	SGW-102	Wall or Ceiling Mounted	POE	Advanced Energy Monitoring Control	Connects to Silvair Controls. Gateway is not required.