


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 86.17 lm/W			
MODEL		I _{max} (cd)	1372	S/MH(C0/180)	0.60
NOMINAL POWER(W)	8	LOR(%)	100.0	S/MH(C90/270)	0.59
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	643.95	η UP,DN(C0-180)	0.0,51.6
NOMINAL FLUX(lm)	643.947	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,48.4
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	120	η down (%)	100.0	CIBSE SHR MAX	0.65

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1174	1180	1168	1142	1132	1129	1138	1163	0- 10	120.7	120.7	18.7,18.7
20	626.0	659.5	653.8	609.2	589.1	580.4	582.3	596.1	10- 20	243.3	364.0	56.5,56.5
30	205.7	226.7	236.2	206.9	194.2	185.8	191.9	197.1	20- 30	172.5	536.5	83.3,83.3
40	35.95	42.01	46.45	42.01	37.90	38.67	39.02	38.11	30- 40	57.28	593.7	92.2,92.2
50	22.09	22.27	22.32	22.15	22.04	21.85	21.73	21.94	40- 50	22.35	616.1	95.7,95.7
60	11.99	12.21	12.26	12.04	12.02	11.96	11.85	11.95	50- 60	14.94	631.0	98,98
70	6.352	6.122	5.338	5.930	6.256	5.931	5.279	6.050	60- 70	8.766	639.8	99.4,99.4
80	2.363	1.524	0.8057	1.392	2.228	1.381	0.7789	1.449	70- 80	3.737	643.5	99.9,99.9
90	0.0060	0.0023	0.0007	0.0043	0.0124	0.0117	0.0087	0.0103	80- 90	0.4176	643.9	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3℃
 Operators:
 Test Date:2022-02-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	35	3
80	122	42
75	144	97
70	167	140
65	191	182
60	216	221
55	261	263
50	309	312
45	352	382


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity: 65.0%
Test Distance: 3.080m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Coefficients of Utilization(CU)														
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00														
1.0	1.11	1.09	1.07	1.09	1.07	1.05	1.05	1.03	1.02	1.01	1.00	.99	.98	.97	.96	.94														
2.0	1.04	1.01	.97	1.03	.99	.96	.99	.97	.94	.96	.94	.92	.94	.92	.90	.89														
3.0	.98	.94	.90	.97	.93	.89	.94	.91	.88	.92	.89	.86	.90	.87	.85	.84														
4.0	.93	.88	.84	.92	.87	.83	.90	.86	.82	.88	.84	.81	.86	.83	.81	.79														
5.0	.88	.83	.79	.87	.82	.78	.85	.81	.78	.84	.80	.77	.82	.79	.76	.75														
6.0	.83	.78	.74	.83	.78	.74	.81	.77	.74	.80	.76	.73	.79	.75	.73	.71														
7.0	.80	.74	.70	.79	.74	.70	.78	.73	.70	.77	.73	.70	.75	.72	.69	.68														
8.0	.76	.71	.67	.75	.70	.67	.74	.70	.67	.73	.69	.66	.72	.69	.66	.65														
9.0	.73	.67	.64	.72	.67	.64	.71	.67	.64	.70	.66	.63	.70	.66	.63	.62														
10.0	.70	.65	.61	.69	.64	.61	.68	.64	.61	.68	.64	.61	.67	.63	.61	.59														



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.168	.095	.030	.161	.092	.029	.149	.085	.027	.137	.079	.025	.126	.073	.024															
2.0	.159	.087	.027	.153	.084	.026	.143	.079	.025	.133	.075	.023	.124	.070	.022															
3.0	.150	.080	.024	.145	.078	.023	.136	.074	.022	.128	.070	.021	.120	.066	.021															
4.0	.141	.073	.022	.137	.072	.021	.129	.069	.020	.122	.066	.020	.116	.063	.019															
5.0	.133	.068	.020	.130	.067	.019	.123	.064	.019	.117	.062	.018	.112	.060	.018															
6.0	.127	.063	.018	.124	.062	.018	.118	.060	.018	.112	.058	.017	.107	.057	.017															
7.0	.120	.060	.017	.118	.059	.017	.113	.057	.016	.108	.055	.016	.104	.054	.016															
8.0	.115	.056	.016	.112	.055	.016	.108	.054	.015	.104	.053	.015	.100	.051	.015															
9.0	.110	.053	.015	.108	.052	.015	.104	.051	.015	.100	.050	.014	.096	.049	.014															
10.0	.105	.050	.014	.103	.050	.014	.100	.049	.014	.096	.048	.014	.093	.047	.013															

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.146	.135	.125	.100	.093	.087	.057	.054	.050	.018	.017	.016	
2.0	.154	.133	.114	.132	.114	.099	.091	.079	.069	.052	.046	.040	.017	.015	.013	
3.0	.141	.113	.091	.121	.098	.079	.083	.068	.056	.048	.040	.033	.015	.013	.011	
4.0	.130	.099	.074	.112	.085	.065	.077	.059	.046	.044	.035	.027	.014	.011	.009	
5.0	.121	.087	.062	.104	.075	.054	.071	.052	.038	.041	.031	.022	.013	.010	.007	
6.0	.113	.077	.052	.097	.067	.045	.067	.047	.032	.039	.028	.019	.013	.009	.006	
7.0	.106	.069	.044	.091	.060	.038	.063	.042	.027	.037	.025	.016	.012	.008	.005	
8.0	.100	.063	.038	.086	.055	.033	.059	.038	.023	.035	.023	.014	.011	.007	.005	
9.0	.094	.058	.033	.081	.050	.029	.056	.035	.020	.033	.021	.012	.011	.007	.004	
10.0	.090	.053	.029	.077	.046	.025	.054	.032	.018	.031	.019	.011	.010	.006	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm										
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH					TYPE:			WEIGHT:		
SPEC.: 3500K					DIM.:			SERIAL No.:		
MFR.: Envisionled					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	4.8	5.6	5.0	5.8	5.9	5.3	6.1	5.5	6.3	6.4
3H	5.3	6.1	5.6	6.3	6.5	5.6	6.4	5.9	6.6	6.8
4H	5.5	6.3	5.8	6.5	6.7	5.7	6.4	5.9	6.6	6.8
6H	5.6	6.3	5.9	6.6	6.8	5.6	6.3	5.9	6.6	6.8
8H	5.6	6.3	5.9	6.6	6.8	5.6	6.3	5.9	6.5	6.8
12H	5.6	6.3	5.9	6.5	6.8	5.5	6.2	5.9	6.5	6.7
4H 2H	4.9	5.7	5.2	5.9	6.1	5.4	6.1	5.6	6.3	6.6
3H	5.6	6.3	6.0	6.6	6.8	5.8	6.5	6.2	6.8	7.0
4H	5.9	6.5	6.3	6.8	7.1	6.0	6.6	6.3	6.8	7.2
6H	6.1	6.7	6.5	7.0	7.3	5.9	6.5	6.3	6.8	7.1
8H	6.1	6.6	6.5	7.0	7.3	5.9	6.4	6.3	6.7	7.1
12H	6.1	6.6	6.5	6.9	7.3	5.8	6.3	6.3	6.7	7.0
8H 4H	5.9	6.4	6.3	6.8	7.1	6.0	6.4	6.4	6.8	7.2
6H	6.2	6.6	6.6	7.0	7.4	6.0	6.4	6.4	6.8	7.2
8H	6.2	6.6	6.7	7.0	7.4	5.9	6.3	6.4	6.7	7.1
12H	6.2	6.5	6.7	7.0	7.4	5.9	6.2	6.3	6.6	7.1
12H 4H	5.9	6.3	6.3	6.7	7.1	5.9	6.4	6.3	6.7	7.1
6H	6.2	6.5	6.6	6.9	7.4	5.9	6.3	6.4	6.7	7.1
8H	6.2	6.5	6.7	6.9	7.4	5.9	6.2	6.4	6.6	7.1
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.5 / - 0.7					+ 1.2 / - 1.2				
1.5H	+ 0.5 / - 0.4					+ 1.9 / - 0.7				
2.0H	+ 0.8 / - 0.8					+ 1.1 / - 0.9				

CIE Pub.117, 643.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.5)
Area: 0.111111 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	87	80	76	86	80	76	85	80	76	73
0.80	94	88	84	93	88	84	92	87	84	80
1.00	99	93	89	98	92	89	96	92	88	84
1.25	103	97	94	102	97	93	100	96	93	88
1.50	105	101	97	104	100	97	102	98	95	91
2.00	108	104	101	107	103	100	104	101	98	93
2.50	110	106	103	108	105	102	105	102	100	94
3.00	111	108	105	110	107	104	106	104	102	95
4.00	114	111	109	112	109	107	108	106	104	97
5.00	115	113	111	113	111	109	109	107	106	98
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3 °C
Operators:
Test Date: 2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity: 65.0%
Test Distance: 3.080m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

AAI Figure

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:119.94V I:0.0848A P:7.4732W PF:0.9483 Freq:59.98Hz Lamp Flux:643.947x1 lm		
NAME: LED-DLJBX-TML-2SQ-8W-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: Envisionled	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	191
L_0~180 (75) av	142
L_0~180 (85) av	31
L_90~270 (65) av	181
L_90~270 (75) av	96
L_90~270 (85) av	3
L_45 (65) av	191
L_45 (75) av	121
L_45 (85) av	6

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-02-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3 °C
Operators:
Test Date: 2022-02-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity: 65.0%
Test Distance: 3.080m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:3.080m [K=1.0000]
Remarks:

```