


4" & 6" LED Slim Panels

Fire Rated Series



Project: _____ Part #: _____
Type: _____

Canless Downlights



FIRE RATED



Detail Specifications:

- Fire Rated: 2 hour fire rating
- Finish: White, Black, Bronze, Brushed Nickel, Custom
- Wet Location Rated
- Beam Angle: 110°
- Chip: SMD 2835, R9 >50, CRI >90
- 3 Step MacAdam Ellipses
- Operating Temperature: -40° - 114° F
- Lens: Acrylic frosted, non-yellowing
- Average life (L70) of 50,000 hours

Applications:

- General Recessed Lighting
- Residential & Multifamily
- Office and Meeting Rooms
- Education, Healthcare, Retail, Hospitality

Product Information:

- 5-CCT Selectable: 27/30/35/40/50K
- Edge-lit technology: reduces glare with even light distribution
- Perfect for shallow ceilings. Only 1.5" space required.
- Metal housing and trim for better heat dissipation
- Standard white round trim included: optional trims available
- Optional emergency backup available: delivers full lumens in EM mode up to 25W
- SnapTrim Canless: Spring clips with remote j-box eliminates can

Driver Options:

- Voltage: 120V
- Triac Dimmable down to 5%
- Built in 2.5Kv Surge Protector
- Flicker Free

Mounting & Installation:

- Cut Out Dimensions:
 - 4": 4-1/4"
 - 6": 6-1/4"
- Optional new construction plate available
- This fixture does not fit into a recessed can
- No can needed in remodel applications, tension clips mount into 1/2" to 1.5" thick ceiling
- Can be removed from below the ceiling for service or replacement
- Pre-wired junction box with circuit wiring built in (3 in / 3 out)

Certifications:

- ETL Listed for USA and CA
- Energy Star Certified
- CA Title 24 JA8-2022 CEC Listed
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017
- IC Rated and ASTM-E283 Air-Tight
- Complies with UL 263, ASTM E119, CAN ULC S101

Series

LED-SL-PNL-4R-12W-5CCT-FR-WH
12W • 840lm
LED-SL-PNL-6R-15W-5CCT-FR-WH
15W • 1150lm

Emergency

(Blank)
No Emergency
Backup
EMB
Emergency
Backup

Optional Accessories (Order Separately)

Trim

SLPNL-TRIM-4R-BLK
Black
SLPNL-TRIM-4R-BRZ
Bronze
SLPNL-TRIM-4R-BNI
Brushed Nickel
SLPNL-TRIM-6R-BLK
Black
SLPNL-TRIM-6R-BRZ
Bronze
SLPNL-TRIM-6R-BNI
Brushed Nickel

New Construction Plates

CUNV-NC-ICAT-7H
Universal plate w/ hanging bars
C4-JBX-RI
4" Rough in plate
C6-JBX-RI
6" Rough in plate
CUNV-JBX-RI-XL
Universal rough in plate. Extra long

Extension Cables

JBX-EXT-6'-TRI
6' Extension
JBX-EXT-10'-TRI
10' Extension
JBX-EXT-12'-TRI
12' Extension

Emergency Backup ¹ (field install)


LED-EMB-15W-HV
-0/10V-2P
Up to 14W fixtures
LED-EMB-25W-HV
-0/10V-2P
Up to 24W fixtures

1. Field installable. Lasts 90 minutes.



Specs and model numbers are subject to change with or without notice.

4" & 6" LED Slim Panels Fire Rated Series

FEATURES







DIMENSIONS



4" & 6" LED Slim Panels Fire Rated Series

ACCESSORIES



Model	Voltage	Watts	Lumens	Color	CRI
LED-SL-PNL-4R-12W-5CCT-FR-WH	120V	12w	840	27/30/35/40/50K	>90
LED-SL-PNL-6R-15W-5CCT-FR-WH	120V	15w	1150	27/30/35/40/50K	>90

TRIMS

Accessory Model	Description
SLPNL-TRIM-4R-BLK	4" Round Black Trim
SLPNL-TRIM-4R-BRZ	4" Round Bronze Trim
SLPNL-TRIM-4R-BNI	4" Round Brushed Nickel Trim
SLPNL-TRIM-6R-BLK	6" Round Black Trim
SLPNL-TRIM-6R-BRZ	6" Round Bronze Trim
SLPNL-TRIM-6R-BNI	6" Round Brushed Nickel Trim

CONSTRUCTION PLATES

Accessory	Description
CUNV-NC-ICAT-7H	1" 2" 3" 3.5" 4" 5" 6" Universal Pre-Mounting New Construction Plate
C4-JBX-RI	4" Rough In Plate
C6-JBX-RI	6" Rough In Plate
CUNV-JBX-RI-XL	Universal tough in plate (Extra Long)

EXTENSION CABLE

Accessory	Description
JBX-EXT-6'-TRI	6" Extension Cable
JBX-EXT-10'-TRI	10" Extension Cable
JBX-EXT-12'-TRI	12" Extension Cable

BATTERY BACK-UP

Accessory	Description
LED-EMB-15W-HV-0/10V-2P	Up to 14W fixtures
LED-EMB-25W-HV-0/10V-2P	Up to 24W fixtures

