


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 80.60 lm/W			
MODEL		I _{max} (cd)	3286	S/MH(C0/180)	0.44
NOMINAL POWER(W)	15	LOR(%)	100.0	S/MH(C90/270)	0.61
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	1062.5	η UP,DN(C0-180)	0.0,41.9
NOMINAL FLUX(lm)	1062.48	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,58.1
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	120	η down (%)	100.0	CIBSE SHR MAX	0.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	2395	1980	1695	1672	1948	2336	2687	2757	0- 10	244.5	244.5	23,23
20	1093	775.6	588.8	576.0	763.5	1082	1403	1419	10- 20	423.6	668.1	62.9,62.9
30	266.7	252.3	169.3	197.5	197.3	269.4	339.2	378.7	20- 30	246.0	914.1	86,86
40	51.58	56.30	43.07	49.85	44.29	67.31	57.02	96.31	30- 40	78.70	992.8	93.4,93.4
50	28.30	34.30	25.53	31.93	26.76	36.93	29.14	38.60	40- 50	31.84	1025	96.4,96.4
60	13.13	16.32	13.59	15.94	13.54	16.88	13.00	17.52	50- 60	19.95	1045	98.3,98.3
70	5.989	7.916	6.858	8.599	6.726	7.533	5.728	7.136	60- 70	10.55	1055	99.3,99.3
80	3.279	3.989	4.063	4.553	4.076	3.571	2.835	3.185	70- 80	5.452	1061	99.8,99.8
90	0.0322	0.0300	0.0368	0.0300	0.0100	0.0104	0.0201	0.0146	80- 90	1.898	1062	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.09	1.07	1.09	1.07	1.06	1.05	1.04	1.02	1.02	1.01	.99	.98	.97	.96	.95
2.0	1.05	1.01	.98	1.03	1.00	.97	1.00	.98	.95	.97	.95	.93	.95	.93	.91	.90
3.0	.99	.95	.92	.98	.94	.91	.95	.92	.89	.93	.90	.88	.91	.89	.87	.85
4.0	.94	.89	.86	.93	.89	.85	.91	.87	.84	.89	.86	.83	.87	.85	.82	.81
5.0	.90	.85	.81	.89	.84	.81	.87	.83	.80	.86	.82	.79	.84	.81	.79	.77
6.0	.86	.81	.77	.85	.80	.77	.83	.79	.76	.82	.79	.76	.81	.78	.75	.74
7.0	.82	.77	.73	.81	.77	.73	.80	.76	.73	.79	.75	.72	.78	.75	.72	.71
8.0	.79	.74	.70	.78	.73	.70	.77	.73	.70	.76	.72	.69	.75	.72	.69	.68
9.0	.75	.71	.67	.75	.70	.67	.74	.70	.67	.73	.70	.67	.73	.69	.67	.65
10.0	.73	.68	.65	.72	.68	.65	.72	.67	.64	.71	.67	.64	.70	.67	.64	.63



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.161	.092	.029	.155	.088	.028	.142	.082	.026	.131	.075	.024	.120	.070	.022		
2.0	.151	.083	.025	.146	.080	.025	.135	.075	.023	.126	.071	.022	.117	.066	.021		
3.0	.142	.076	.023	.137	.074	.022	.129	.070	.021	.121	.066	.020	.113	.063	.019		
4.0	.134	.070	.020	.130	.068	.020	.122	.065	.019	.115	.062	.019	.109	.059	.018		
5.0	.126	.064	.019	.123	.063	.018	.116	.061	.018	.110	.058	.017	.105	.056	.017		
6.0	.120	.060	.017	.117	.059	.017	.111	.057	.017	.106	.055	.016	.101	.053	.016		
7.0	.114	.056	.016	.111	.055	.016	.106	.054	.015	.102	.052	.015	.097	.051	.015		
8.0	.108	.053	.015	.106	.052	.015	.102	.051	.015	.098	.050	.014	.094	.048	.014		
9.0	.104	.050	.014	.102	.050	.014	.098	.048	.014	.094	.047	.013	.091	.046	.013		
10.0	.099	.048	.013	.097	.047	.013	.094	.046	.013	.091	.045	.013	.088	.044	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.170	.157	.146	.145	.135	.126	.100	.093	.087	.057	.054	.051	.018	.017	.016		
2.0	.154	.133	.115	.131	.114	.099	.090	.079	.069	.052	.046	.041	.017	.015	.013		
3.0	.140	.113	.092	.120	.098	.080	.082	.068	.056	.048	.040	.033	.015	.013	.011		
4.0	.128	.098	.076	.110	.085	.066	.076	.059	.046	.044	.035	.027	.014	.011	.009		
5.0	.119	.086	.063	.102	.075	.054	.070	.052	.038	.041	.031	.023	.013	.010	.008		
6.0	.110	.077	.053	.095	.067	.046	.065	.047	.032	.038	.027	.019	.012	.009	.006		
7.0	.103	.069	.045	.089	.060	.039	.061	.042	.028	.036	.025	.016	.012	.008	.005		
8.0	.097	.062	.039	.084	.054	.034	.058	.038	.024	.034	.022	.014	.011	.007	.005		
9.0	.092	.057	.034	.079	.049	.029	.055	.035	.021	.032	.021	.012	.010	.007	.004		
10.0	.087	.052	.029	.075	.045	.026	.052	.032	.018	.030	.019	.011	.010	.006	.004		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm											
NAME: 4寸白色方形trimless						TYPE:		WEIGHT:			
SPEC.: 3500K						DIM.:		SERIAL No.:			
MFR.: ENVISION LIGHTING						SUR.:		Shielding Angle:			
ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		3.3	4.1	3.5	4.3	4.4	2.2	3.0	2.4	3.2	3.3
3H		3.6	4.4	3.9	4.6	4.8	2.8	3.5	3.0	3.7	3.9
4H		3.7	4.4	4.0	4.7	4.9	3.0	3.7	3.3	3.9	4.1
6H		3.9	4.5	4.2	4.8	5.0	3.3	4.0	3.6	4.2	4.5
8H		4.0	4.6	4.3	4.9	5.1	3.5	4.1	3.8	4.4	4.6
12H		4.0	4.6	4.3	4.9	5.2	3.5	4.2	3.9	4.4	4.7
4H 2H		3.5	4.2	3.7	4.4	4.6	2.5	3.2	2.8	3.4	3.6
3H		3.9	4.5	4.2	4.8	5.1	3.2	3.8	3.5	4.1	4.4
4H		4.1	4.7	4.5	5.0	5.3	3.6	4.1	3.9	4.4	4.7
6H		4.4	4.9	4.8	5.2	5.6	4.1	4.6	4.4	4.9	5.2
8H		4.5	5.0	4.9	5.3	5.7	4.3	4.7	4.7	5.1	5.4
12H		4.6	5.1	5.1	5.4	5.8	4.4	4.8	4.8	5.2	5.6
8H 4H		4.2	4.7	4.6	5.0	5.4	3.7	4.2	4.1	4.5	4.9
6H		4.6	5.0	5.0	5.4	5.8	4.4	4.7	4.8	5.1	5.5
8H		4.8	5.2	5.3	5.6	6.0	4.7	5.0	5.1	5.4	5.9
12H		5.1	5.3	5.5	5.8	6.3	4.8	5.1	5.3	5.6	6.0
12H 4H		4.2	4.6	4.6	5.0	5.4	3.7	4.1	4.1	4.5	4.9
6H		4.7	5.0	5.1	5.4	5.9	4.4	4.7	4.8	5.2	5.6
8H		4.9	5.2	5.4	5.7	6.1	4.7	5.0	5.2	5.5	5.9
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H		+ 0.7 / - 0.9					+ 0.5 / - 0.6				
1.5H		+ 0.6 / - 0.7					+ 0.3 / - 0.6				
2.0H		+ 1.1 / - 1.2					+ 0.8 / - 0.8				

CIE Pub.117, 1062 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.2)
Area: 0.111111 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	87	81	77	87	81	77	86	81	77	74
0.80	95	89	85	94	89	85	93	88	85	81
1.00	99	94	90	98	93	90	97	93	89	85
1.25	103	98	94	102	97	94	100	96	93	89
1.50	106	101	98	105	100	97	102	99	96	92
2.00	108	104	101	107	103	100	104	101	99	94
2.50	110	106	103	109	105	102	105	103	100	95
3.00	112	108	105	110	107	104	107	104	102	96
4.00	114	111	109	112	109	107	108	106	105	98
5.00	115	113	111	113	111	109	109	107	106	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3℃
Operators:
Test Date: 2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3℃
 Operators:
 Test Date:2022-06-23

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity:65.0%
 Test Distance:3.090m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.20V I:0.1113A P:13.182W PF:0.9853 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1062.48x1 lm		
NAME: 4寸白色方形trimless	TYPE:	WEIGHT:
SPEC.: 3500K	DIM.:	SERIAL No.:
MFR.: ENVISION LIGHTING	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	204
L_0~180 (75) av	155
L_0~180 (85) av	213
L_90~270 (65) av	203
L_90~270 (75) av	154
L_90~270 (85) av	152
L_45 (65) av	239
L_45 (75) av	184
L_45 (85) av	174

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:
Test Date:2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3 °C
Operators:
Test Date: 2022-06-23

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity: 65.0%
Test Distance: 3.090m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.090m [K=1.0000]
Remarks:

```