

PAR SERIES: 5-CCT LED BULBS

PAR-20, PAR-30, PAR-38






PAR20



PAR30



PAR38



Detail Specifications

- IP Rating: Damp Location
- Beam Angle: 40°
- 5-CCT: 27/30/35/40/50K
- Chip: SMD 2835, R9 >50, CRI >90
- Operating Temperature: -4° - 114° F
- Average life (L70) of 25,000 hours

Applications:

- Can Lights
- Track Lighting
- Interior Lighting
- Downlighting
- Showcases
- Residential, Commercial and Industrial

Product Information:

- Suitable for use in existing fixtures
- Instant-On to full brightness

Driver Options:

- 120V
- Triac Dimmable
- PF >0.9, 50/60Hz

Mounting & Installation:

- E26 Socket
- Direct BR Lamp Replacement

Packaging:

- All bulbs come in individual color boxes, but are sold in inner carton qty packs only

Carton Qty.	P20	P30	P38
Inner Carton	10	6	6
Master Carton	100	48	48

Certifications:

- ETL Listed for USA and CA
- Energy Star
- Title 20 and JA8-2022 Approved
- 3 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

Dimmer List:

Leviton	6674
Lutron	LGCL-153P
Lutron	DVCL-153P
Lutron	CTCL-153P
Lutron	MAELV-300

Series

LED-P20-7W-5CCT

450 Lumens 50W Equivalent

LED-P30-10W-5CCT

750 Lumens 75W Equivalent

LED-P38-13W-5CCT

1,000 Lumens 100W Equivalent

Specs and model numbers are subject to change with or without notice.