

RESIDENTIAL ACCESSORIES

AIR CONDITIONER WHIPS

- Meets the requirements of the 2011 National Electrical Code: Articles 310.10 (C) (H) (2) and (4), Table 310.15 (B) (2) (A), 356.10, 356.20, 440.6 and 440.31.
- Labor and Time Savings! Cost effective Non-Metallic AC Whips save the Contractor time and money.
- Reducing washers included.
- Convenient packaging of 10 or 20 AC Whips per Carton.
- UL Listed. File Number: E87199

Designed to save the Contractor installation time and labor, EPCO's Air Conditioner Whips are typically used to connect the Central Air Conditioner Compressor to the AC disconnect box. Air Conditioner Whips include one (1) Straight and one (1) 90° Connector. Three (3) Conductors are included in 1/2" or 3/4" Non-Metallic Liquid Tight Conduit using either 8 or 10 AWG THHN Conductors.

EPCO will also build "custom" Air Conditioner Whips to your specifications in any length using UL Listed components. Contact EPCO Inside Sales for more specific information.



Catalog Number	UPC Number	Description	Order Unit	Order Qty	Unit Pkg	Units/Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
ACWNM1043-1RA	11202	AC Whip: 4 FT, 1/2", one (1) Straight and one (1) Right Angle Connector, three (3) 10 AWG Stranded - Red, Black, Green	EA	20	BRL	0	0	1	No	47
ACWNM1063-1RA	11204	AC Whip: 6 FT, 1/2", one (1) Straight and one (1) Right Angle Connector, three (3) 10 AWG Stranded - Red, Black, Green	EA	20	BRL	0	0	1	No	49
ACWNM843-1RA	11205	AC Whip: 4 FT, 3/4", one (1) Straight and one (1) Right Angle Connector, two (2) 8 AWG Stranded - Red, Black; one (1) 10 AWG Stranded - Green	EA	20	BRL	0	0	1	No	49
ACWNM863-1RA	11208	AC Whip: 6 FT, 3/4", one (1) Straight and one (1) Right Angle Connector, two (2) 8 AWG Stranded - Red, Black; one (1) 10 AWG Stranded - Green	EA	10	BRL	0	0	1	No	36
ACWNM843-1RA-1/2	11214	AC Whip: 4 FT, 1/2", one (1) Straight and one (1) Right Angle Connector, two (2) 8 AWG Stranded - Red, Black; one (1) 10 AWG Stranded - Green	EA	20	BRL	0	0	1	No	49
ACWNM863-1RA-1/2	11213	AC Whip: 6 FT, 1/2", one (1) Straight and one (1) Right Angle Connector, two (2) 8 AWG Stranded - Red, Black; one (1) 10 AWG Stranded - Green	EA	20	BRL	0	0	1	No	50

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BRL (Barrel); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the Units per Carton

Specifications subject to change without prior notice.



EPCO AC Whips and AC Whip Connectors are Made in the USA. Complies with the American Recovery and Reinvestment Act – Buy American Provision.

www.engproducts.com

5401 SMETANA DRIVE | MINNETONKA, MN 55343

P 800.336.1976 | F 800.336.2801



**ENGINEERED
PRODUCTS CO.**


RESIDENTIAL ACCESSORIES

POWER/APPLIANCE CORDS

- UL Listed.
- Meets the requirements of the 2011 National Electrical Code: Articles 422.16(B)(1) and (2).

SPT Flat and SJT Round Power/Appliance Cords are used for typical applications such as installation of garbage disposals, dishwashers or similar appliances. These Power/Appliance Cords can also be used for repairs of appliances, power tools or other electrical equipment.

The cords are 16 AWG or 14 AWG 3 wire heavy-duty vinyl conductors. One end is pre-stripped at the factory, the other end has a straight or right angle grounded male plug.



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
SPT 16/3 Flat Cord										
PCR3	10178	3 FT: Right Angle Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	8
PCR4	10180	4 FT: Right Angle Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	8
PCR6	10181	6 FT: Right Angle Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	12
PCR8	10182	8 FT: Right Angle Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	13
PCS3	10179	3 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	8
PCS4	10183	4 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	8
PCS6	10184	6 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	12
PCS8	10185	8 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	13
PCS12	10169	12 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	22
SJT 16/3 Round Cord										
PSS3	10186	3 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	8
PSS4	10168	4 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	8
PSS6	10187	6 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	12
PSS8	10188	8 FT: Straight Plug, 13 AMP - Black	EA	25	BX	0	0	25	Yes	13
SPT 16/3 Round Cord										
RSS3	10219	3 FT: Straight Plug with Receptacle, 15 AMP - Black	EA	25	BX	0	0	25	Yes	12
SPT 14/3 Flat Cord										
10950	10950	3 FT: Straight Plug, 15 AMP - Beige	EA	25	BX	0	0	25	Yes	9
10953	10953	6 FT: Straight Plug, 15 AMP - Beige	EA	25	BX	0	0	25	Yes	17
10956	10956	9 FT: Straight Plug, 15 AMP - Beige	EA	25	BX	0	0	25	Yes	25

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BRL (Barrel); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton

Specifications subject to change without prior notice.

RANGE CORDS

- Meets Canadian Standards Association (CSA) Approval.
- Meets the requirements of the 2011 National Electrical Code: Articles 420.5, 422.16(B)(3)(4) and 422.33(A) and (B).
- Heavy-duty terminals ensure an excellent power quality connection.
- Right angle plug for fit-to-wall.
- Strain Relief protects Range Cord from damage.



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
40000	40000	Range Cord: 4 FT, SRDT 6/2 and 8/1, 3 Wire, 50 AMP - Gray	EA	16	BX	0	0	1	No	27
40001	40001	Range Cord: 6 FT, SRDT 6/2 and 8/1, 3 Wire, 50 AMP - Gray	EA	16	BX	0	0	1	No	35
40010	40010	Range Cord: 4 FT, SRDT 6/2 and 8/2, 4 Wire, 50 AMP - Black	EA	12	BX	0	0	1	No	33
40011	40011	Range Cord: 6 FT, SRDT 6/2 and 8/2, 4 Wire, 50 AMP - Black	EA	12	BX	0	0	1	No	38

DRYER CORDS

- Meets Canadian Standards Association (CSA) Approval.
- Meets the requirements of the 2011 National Electrical Code: Articles 420.5, 422.16(B)(3)(4) and 422.33(A) and (B).
- Heavy-duty terminals ensure an excellent power quality connection.
- Right angle plug for fit-to-wall.
- Strain Relief protects Dryer Cord from damage.



Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/ Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
40020	40020	Dryer Cord: 4 FT, SRDT 10/3, 3 Wire, 30 AMP - Gray	EA	32	BX	0	0	1	No	35
40021	40021	Dryer Cord: 6 FT, SRDT 10/3, 3 Wire, 30 AMP - Gray	EA	32	BX	0	0	1	No	51
40030	40030	Dryer Cord: 4 FT, SRDT 10/4, 4 Wire, 30 AMP - Black	EA	16	BX	0	0	1	No	27
40031	40031	Dryer Cord: 6 FT, SRDT 10/4, 4 Wire, 30 AMP - Black	EA	16	BX	0	0	1	No	35

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; **Order Qty:** Number of pieces in each Unit; **Unit Pkg:** Packaging types - BG (Bag), BX (Box), BRL (Barrel); **Units/Case:** Unit packages contained in the Case; **TL Case Qty:** The total number of items in each Master Case; **Min Order Qty:** The smallest Unit that can be ordered; **MM Req:** Must order multiples of the Unit in the stated quantities; **Ship Wt (Lbs):** Total weight of the units per Carton

Specifications subject to change without prior notice.

NON-METALLIC UF AND STRAIN RELIEF CORD CONNECTORS

- Compression type specifically designed for use with 14/2 or 12/2 AWG Romex® cable.
- Low profile design to fit the new smaller UF Cables as well as standard sizes.



Catalog Number	UPC Number	Description	Order Unit	Order Qty	Unit Pkg	Units/Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
Non-Metallic UF Connectors										
15035	15035	Non-Metallic UF Connector - 1/2": Accommodates 14/2 and 12/2 Romex Cable and EPCO SPT 16/3 Flat Power/Appliance Cords	EA	12	BG	0	0	12	Yes	1
15040	15040	Non-Metallic UF Connector - 3/4": Accommodates 14/3 and 10/2 Romex Cable and EPCO SPT 16/3 Flat Power/Appliance Cords	EA	12	BG	0	0	12	Yes	1
Non-Metallic Strain Relief Cord Connectors										
15042	15042	Non-Metallic Strain Relief Cord Connector - 1/2": Accommodates EPCO SPT 16/3 Round Power/Appliance Cords	EA	12	BG	0	0	12	Yes	1
15044	15044	Non-Metallic Strain Relief Cord Connector - 3/4": Accommodates EPCO SPT 16/3 Round Power/Appliance Cords	EA	12	BG	0	0	12	Yes	1

WALL PLATE INSULATION GASKET

Energy saving gasket prevents heat and cold loss through outlets and switches that are located on outside walls.

- Easy to install. Only a screwdriver is required.
- Flame retardant closed cell polyethylene insulating foam.
- One-piece design fits toggle, duplex receptacle or Decora style wall plates.
- Fits duplex receptacles and multi-gang boxes.

Note: Each gasket is perforated.



Catalog Number	UPC Number	Description	Order Unit	Order Qty	Unit Pkg	Units/Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
10938	10938	Wall Plate Insulation Gasket	EA	100	BG	0	0	100	Yes	2

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BRL (Barrel); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the Units per Carton

Specifications subject to change without prior notice.

©2012 Engineered Products Company. All Rights Reserved. Romex is a registered trademark of Southwire. A1 (6/12-SP)

www.engproducts.com

5401 SMETANA DRIVE | MINNETONKA, MN 55343
P 800.336.1976 | F 800.336.2801



**ENGINEERED
PRODUCTS CO.**