GE Lighting

67566 - 4-1 - F54T5HO 120 to 277 UltraStart PRS High Temp F Can; High Efficiency T5 ballast with Continuous Cathode Cutout Technology

GE454MVPS90-F

- Lower Maintenance Costs with Parallel Lamp Operation
- Multi-Voltage technology means a single ballast handles voltage from 108V to 305V
- Auto-Restart withstands temporary losses in power without the need to cycle power
- UltraCool™ Operation 90C case rating/UL Approved 55C Ambient Rating
- Individual lamp End of Lamp Life protection - only one lamp shuts down at end of life
- Anti-Striation Control for better light quality, with no striations.
- Cold temperature -20F Minimum Starting Temperature

Product Photo



SAFETY & PERFORMANCE

- Pro_comp_res_req
- UL_Amb_App
- UL_type_1
- ANSI_C82
- UL_Type_HL
- FCC_CS_NCons
- UL_Cls_P
- C_max_wty_temp
- Type_CC

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
	3	277	163	0.6	0.93		0.98	1.4	8	-20
F58T8	2	120	110	0.92			0.99	1.4	10	-20
F58T8	1	120	66	0.57			0.99	1.4	12	-20
F58T8	2	277	110	0.41			0.98	1.4	8	-20
F58T8	1	277	66	0.29			0.9	1.4	23	-20
F54T5/HO	1	120	69	0.57	1.16		0.99	1.4	12	-20
F54T5/HO	1	277	69	0.27	1.16		0.9		1	-20
F54T5/HO	2	120	118	0.99	0.96		0.98	1.4	10	-20
F54T5/HO	2	277	117	0.43	0.96		0.96	1.4	9	0
F54T5/WM	4	277	213	0.78	1.0		0.99	1.4	8	0
F54T5/WM	3	120	163	1.36	0.98		1.0	1.4	8	0
F54T5/WM	4	277	216	1.83	1.0		0.99	1.4	8	0
F54T5/WM	4	120	214	1.79	1.0		1.0	1.4	7	0
F54T5/WM	2	120	112	0.94	0.99		0.99	1.4	10	0
F54T5/WM	1	277	67	0.3	1.12		0.9	1.4	23	0
F54T5/WM	1	120	66	0.58	1.12		0.99	1.4	12	0
FT55W/4P	1	120	65	0.54	0.91		0.99	1.4	12	0
FT55W/4P	2	120	108	0.91	0.88		0.99	1.4	10	0
F54T5/HO	3	120	165	1.38	0.93		1.0	1.4	8	-20
F54T5/HO	4	120	220	1.84	1.0		1.0	1.4	7	-20
F54T5/WM	3	277	161	0.59	0.98		0.98	1.4	9	0

F54T5/WM	3	277	163	0.6	0.93		0.98	1.4	8	-20
F58T8	3	120	159	1.34			1.0	1.4	9	-20
F58T8	4	120	208	1.74			1.0	1.4	7	-20
F58T8	3	277	157	0.58			0.98	1.4	9	-20
F58T8	4	277	205	0.76			0.99	1.4	9	-20
FT50W/4P	1	120	68	0.57	1.19		0.99	1.4	12	0
FT50W/4P	1	277	69	0.27	1.19		0.9	1.4	22	0
FT50W/4P	2	120	117	0.98	1.08		0.99	1.4	10	0
FT50W/4P	2	277	117	0.43	1.08		0.98	1.4	8	0
FT50W/4P	3	120	171	1.43	1.03		1.0	1.4	8	0
FT50W/4P	3	277	169	0.62	1.03		0.98	1.4	9	0
FT50W/4P	4	120	222	1.86	1.07		1.0	1.4	7	0
FT50W/4P	4	277	218	0.81	1.07		0.99	1.4	8	0
FT55W/4P	1	277	66	0.26	0.91		0.89	1.4	23	0
FT55W/4P	2	277	108	0.4	0.88		0.97	1.4	8	0
FT55W/4P	3	120	162	1.36	0.86		1.0	1.4	9	0
FT55W/4P	3	277	160	0.59	0.86		0.98	1.4	9	0
FT55W/4P	4	120	206	1.73	0.86		1.0	1.4	7	0
FT55W/4P	4	277	203	0.75	0.86		0.99	1.4	8	0
F54T5/47W	1	120	64	0.53	1.09		0.99	1.4	13	-20
F54T5/47W	1	277	63	0.26	1.09		0.88	1.4	24	-20
F54T5/47W	2	120	109	0.91	1.03		0.99	1.4	10	-20
F54T5/47W	2	277	109	0.4	1.03		0.98	1.4	8	-20
F54T5/47W	3	120	158	1.32	1.0		1.0	1.4	8	-20
F54T5/47W	4	277	202	0.79	1.0		0.99	1.4	8	-20
F54T5/47W	4	120	206	1.85	1.0		1.0	1.4	7	-20
F54T5/47W	3	277	156	0.57	1.0		0.97	1.4	9	-20
F54T5/WM	2	277	112	0.41	0.99		0.98	1.4	8	0
F54T5/HO	4	277	216	0.8	1.0		0.99	1.4	8	-20