



GE
Lighting

SAFETY & PERFORMANCE

- ☞ cUL_Listed
- ☞ FCC_CS_NCons
- ☞ NR_Can
- ☞ UL_Cls_P
- ☞ UL_Listed
- ☞ UL_Type1_Out
- ☞ UL_Type_HL
- ☞ Pro_comp_res_req

74474 - GE LFL Multi-Volt ProLine™ Electronic Multivolt Instant

Start Ballast

GE260IS-MV-N

- ☞ High performance electronic ballast for all general fluorescent applications
- ☞ Instant start electronic ballast for long lamp starting cycles and low initial cost
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ Light-weight, Low Profile Housing
- ☞ Parallel lamp operation means system maintenance is easier to manage

Product Photo



SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
F48T12	1	120	49	0.43	1.1	2	0.99	1.7	10	0
F48T12	1	277	48	0.2	1.1	2	0.89	1.7	12	0
F48T12	2	120	73	0.65	0.9	1	0.99	1.7	8	0
F48T12	2	277	73	0.29	0.9	1	0.95	1.7	10	0
F60T12	1	120	60	0.53	1.08	2	0.99	1.7	10	0
F60T12	1	277	60	0.28	1.08	2	0.94	1.7	12	0
F60T12	2	120	92	0.81	0.9	1	0.99	1.7	8	0
F60T12	2	277	91	0.35	0.9	1	0.96	1.7	10	0
F64T12	1	277	63	0.25	1.08	2	0.95	1.7	12	0
F64T12	1	120	63	0.55	1.08	2	0.99	1.7	10	0
F64T12	2	120	97	0.86	0.9	1	0.99	1.7	8	0
F64T12	2	277	96	0.37	0.9	1	0.97	1.7	10	0
F72T12	1	120	69	0.6	1.04	2	0.99	1.7	10	0
F72T12	2	120	107	0.94	0.9	1	0.99	1.7	8	0
F72T12	2	277	106	0.4	0.9	1	0.97	1.7	10	0
F72T12	1	277	69	0.27	1.04	2	0.95	1.7	12	0
F84T12	1	120	80	0.7	1.04	1	0.99	1.7	10	0
F84T12	2	277	123	0.47	0.9	1	0.97	1.7	10	0
F84T12	1	277	79	0.3	1.04	1	0.96	1.7	12	0
F84T12	2	120	125	1.1	0.9	1	0.99	1.7	8	0
F96T12	1	120	90	0.79	1.02	1	0.99	1.7	10	0
F96T12	1	277	89	0.34	1.02	1	0.96	1.7	12	0
F96T12	2	120	141	1.24	0.9	1	0.99	1.7	8	0
F96T12	2	277	138	0.53	0.9	1	0.98	1.7	10	0
F96T12/WM	1	120	72	0.63	1.0	1	0.99	1.7	10	60

F96T12/WM	1	277	71	0.28	1.0	1	0.95	1.7	12	60
F96T12/WM	2	120	112	0.98	0.9	1	0.99	1.7	8	60
F96T12/WM	2	277	110	0.42	0.9	1	0.97	1.7	10	60
F96T12/WM P	1	120	68	0.6	1.0	1	0.99	1.7	10	60
F96T12/WM P	1	277	68	0.27	1.0	1	0.95	1.7	12	60
F96T12/WM P	2	120	107	0.94	0.88	1	0.99	1.7	8	60
F96T12/WM P	2	277	106	0.4	0.88	1	0.96	1.7	10	60

Sep 9, 2016 10:53:21 PM For additional information, visit www.gelighting.com