



GE
Lighting

15984 - GE Ecolux® covRguard® Starcoat® T8 - Shatter-Resistant

F25T8SP41ECOCVG

- ☞ A shatter resistant lamp encased in a 15 ml Lexan sleeve.
Complies with FDA food code 6-202 and 21CFR 110.20. NSF and UL certified. Blocks UV lamp emissions from 380 to 180 nm.
- ☞ Passes TCLP, which can lower disposal costs.

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	2.95 mg
Mercury-Picogram per mean lm hr	76.8
Rated Life Instant Start-Hrs	15000 h @ 3 h 20000 h @ 12 h
Rated Life Rapid Start - Hrs	30000 h @ 3 h 36000 h @ 12 h
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	30000 h
Primary Application	Shatter-Resistant Specialty
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	1920 lm
Nominal Initial Lumen per Watt	81
Initial Lumens-nominal	2020 lm
Color Rendering Index-CRI	78
Color Temperature	4100 K

PRODUCT INFORMATION

Product Code	15984
Description	F25T8SP41ECOCVG
Alternative Unit Of Measure	CASE

DIMENSIONS

Bulb Diameter (DIA) <Max>	1.1 in
Bulb Diameter (DIA) <Min>	0.94 in
Diameter	1.0 in
End of Base Pin to Pin	35.67 in
Face to End of Opposing Pin (B) <Max>	35.5 in
Face to End of Opposing Pin (B) <Min>	35.4 in
Nominal Length	36.0 in

CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Turn power off before inspection
installation or removal.