

SWITCH BOXES SINGLE-GANG - 3-1/2" DEEP

Application

- Switch boxes are used to house wiring devices such as switches or outlets


Product Features

- RACO® offers a variety of labor saving mounting brackets that allow for easy positioning of box along studs or joists
- See Box Selection section in the front of this catalog for complete description of bracket types and features
- Gangable switch boxes offer the option of constructing a box to hold two or more devices
- Plaster ears allow the box to be used in "old work" applications


Compliances

- UL – File E195978


All RACO® single gang, two gang, 4" square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult U.L. "Fire Resistance Directory" or the U.L. website at www.ul.com




601, 8601




605



603



600



604, 8604

ORDERING INFORMATION - DIMENSIONS

3" x 2" SWITCH BOXES - 3-1/2" DEEP - GANGABLE WITH NONMETALLIC SHEATHED CABLE CLAMPS - 18.0 CUBIC INCHES							
CATALOG NUMBER	DESCRIPTION BRACKET & SETBACK	SIDE COND.	KNOCKOUTS ENDS		BOTTOM COND.	STD. PKG.	UPC BAR CODE
			CABLE	COND.			
601	Ears	4-1/2"	4	2-1/2"	1-1/2"	25	—
8601	Ears	4-1/2"	4	2-1/2"	1-1/2"	25	
605	TS brkt., 1/2"	4-1/2"	4	2-1/2"	1-1/2"	25	
603	B brkt., 5/8"	4-1/2"	4	2-1/2"	1-1/2"	25	—

3" x 2" SWITCH BOXES - 3-1/2" DEEP - GANGABLE WITH ARMORED CABLE/METAL CLAD/FLEX CLAMPS - 18.0 CUBIC INCHES							
CATALOG NUMBER	DESCRIPTION BRACKET & SETBACK	SIDE COND.	KNOCKOUTS ENDS		BOTTOM COND.	STD. PKG.	UPC BAR CODE
			CABLE	COND.			
600	Ears	4-1/2"	4	2-1/2"	1-1/2"	25	—
604	TS brkt., 1/2"	4-1/2"	4	2-1/2"	1-1/2"	25	—
8604	TS brkt., 1/2"	4-1/2"	4	2-1/2"	1-1/2"	25	

DIMENSIONS			
CATALOG NUMBER	A	B	C
601, 8601	3-1/2"	—	—
605	3-1/2"	7-5/32"	2-5/16"
603	3-1/2"	1-31/32"	4"
600	3-1/2"	—	—
604, 8604	3-1/2"	7-5/32"	2-5/16"

STEEL SWITCH BOXES

