

Application

- Switch boxes are used to house wiring devices such as switches or outlets


Product Features

- RACO® offers a variety of labor saving mounting brackets that allow for easy positioning of box along studs or joists
- See Box Selection section in the front of this catalog for complete description of bracket types and features
- Plaster ears allow the box to be used in "old work" applications


Compliances

- UL – File E195978


All RACO® single gang, two gang, 4" square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult U.L. "Fire Resistance Directory" or the U.L. website at www.ul.com



567



564




570RAC



574



590, 591, 8590



592

ORDERING INFORMATION - DIMENSIONS
**3" x 2" SWITCH BOXES - 2-3/4" DEEP - GANGABLE
WITH NONMETALLIC SHEATHED CABLE CLAMPS - 14.0 CUBIC INCHES**


CATALOG NUMBER	DESCRIPTION BRACKET & SETBACK	SIDE COND.	KNOCKOUTS ENDS		BOTTOM COND.	STD. PKG.	UPC BAR CODE
			CABLE	COND.			
567	Ears	4-1/2"	4	2-1/2"	1-1/2"	50	
564	TS brkt., 1/2"	2-1/2"	4	2-1/2"	1-1/2"	50	

**3" x 2" SWITCH BOXES - 2-3/4" DEEP - GANGABLE
WITH ARMORED CABLE/METAL CLAD/FLEX CLAMPS - 14.0 CUBIC INCHES**

CATALOG NUMBER	DESCRIPTION BRACKET & SETBACK	SIDE COND.	KNOCKOUTS ENDS		BOTTOM COND.	STD. PKG.	UPC BAR CODE
			CABLE	COND.			
570RAC	Ears	4-1/2"	4	2-1/2"	1-1/2"	50	—
574	TS brkt., 1/2"	2-1/2"	4	2-1/2"	1-1/2"	50	

**3" x 2" SWITCH BOXES - 3-1/2" DEEP - GANGABLE
WITH CONDUIT KO'S - 18.0 CUBIC INCHES**

CATALOG NUMBER	DESCRIPTION BRACKET & SETBACK	KNOCKOUTS			STD. PKG.	UPC BAR CODE
		SIDES	ENDS	BOTTOM		
590	Ears	4-1/2"	4-1/2"	1-1/2"	50	—
8590	Ears	4-1/2"	4-1/2"	1-1/2"	50	
591	Ears	4-3/4"	4-3/4"	1-1/2"	50	
592	Without ears	4-1/2"	4-1/2"	1-1/2"	50	—

STEEL SWITCH BOXES

DIMENSIONS

CATALOG NUMBER	A	B	C
567	2-3/4"	—	—
564	2-3/4"	7-5/32"	2-5/16"
570RAC	2-3/4"	—	—
574	2-3/4"	7-5/32"	2-5/16"
590, 8590	3-1/2"	—	—
591	3-1/2"	—	—
592	3-1/2"	—	—