





PolyTuff® I Conduit, Gray or Black



- Rigid PVC core bonded to flexible PVC jacket
- All non-metallic construction ends metal fatigue and separation problems
- Cuts cleanly with a knife or PVC cutter so there are no jagged metal edges
- UL Listed and CSA Certified

PolyTuff® II Tubing, Black



- PVC core with corrugated walls bonded to PVC jacket
- Handles twists, turns, bends, switchbacks and straightaways with ease
- All non-metallic construction ends fatigue and separation problems
- Can be cut with a knife or PVC cutters
- UL Recognized and CSA Certified



G1100



G1100M1

IP66 SUITABILITY			
PolyTuff® I Conduit			
Trade Size (metric designator)	Feet (m)	Gray Catalog Number	Black Catalog Number
3/8 (12)	100 (30.5)	G1038	G1038M1
1/2 (16)	100 (30.5)	G1050	G1050M1
3/4 (21)	100 (30.5)	G1075	G1075M1
1 (27)	100 (30.5)	G1100	G1100M1
1 1/4 (35)	100 (30.5)	G1125	G1125M1
1 1/2 (41)	50 (15.2)	G1150	G1150M1
2 (53)	50 (15.2)	G1200	G1200M1

Note: See pages V-66 and V-67, V-100 and V-101 for approved fittings.
See pages V-102 and V-103 for technical information and dimensional drawings.



B2100

IP66 SUITABILITY		
PolyTuff® II Tubing		
Trade Size (metric designator)	Feet (m)	Catalog Number
1/4 (10)	100 (30.5)	B2025
3/8 (12)	100 (30.5)	B2038
1/2 (16)	100 (30.5)	B2050
3/4 (21)	100 (30.5)	B2075
1 (27)	100 (30.5)	B2100
1 1/4 (35)	100 (30.5)	B2125
1 1/2 (41)	50 (15.2)	B2150
2 (53)	50 (15.2)	B2200

Note: See page V-100 for approved fittings.
See pages V-102 and V-103 for technical information and dimensional drawings.

