Dust-Tight Strain Relief Grips

Aluminum Fittings, Galvanized Steel Mesh, for Insulated Cables

IMPORTANT

Read all breaking strength, safety and technical data relating to this product. Pages V-69 to V-76.

Non-Insulated, Wide Range Strain Relief

Thread Size	Cable Diameter Range Inches	(cm)	Mesh Length @ Nom. Dia. Inches (cm)	Catalog Number
½ NPT	.24"-.32"	(.61-.81)	3.25" (8.25)	**073031200**
½ NPT	.32"-.43"	(.81-1.09)	3.75" (9.52)	**073031201**
½ NPT	.43"-.54"	(1.09-1.37)	4.75" (12.06)	**073031202**
¾ NPT	.54"-.73"	(1.37-1.85)	6.5" (16.51)	**073031203**
1 NPT	.73"-.97"	(1.85-2.46)	7" (17.78)	**073031204**
1¼ NPT	.97"-1.25"	(2.46-3.17)	9" (22.86)	**073031205**
PG29*	.73"-.97"	(1.85-2.46)	7" (17.78)	**073PG291204**

*Note: *Panzergewinde.*



Insulated, Wide Range Strain Relief with Insulating Bushing

Thread Size	Cable Diameter Range Inches	(cm)	Mesh Length @ Nom. Dia. Inches (cm)	Dim. A Inches (cm)	Min. Space Between Grips Inches (cm)	Catalog Number
½ NPS	.24"-.32"	(.61-.81)	3.25" (8.25)	1" (2.54)	1.25" (3.17)	**073031206**
½ NPS	.32"-.43"	(.81-1.09)	3.75" (9.52)	1" (2.54)	1.25" (3.17)	**073031207**
½ NPS	.43"-.54"	(1.09-1.37)	4.75" (12.06)	1" (2.54)	1.25" (3.17)	**073031208**
¾ NPS	.54"-.73"	(1.37-1.85)	6.5" (16.51)	1" (2.54)	1.5" (3.81)	**073031209**
1 NPS	.73"-.97"	(1.85-2.46)	7" (17.78)	1.313" (3.02)	1.75" (4.44)	**073031210**
1¼ NPS	.97"-1.25"	(2.46-3.17)	9" (22.86)	1.313" (3.02)	2.25" (5.71)	**073031211**
1½ NPT	1.25"-1.50"	(3.17-3.81)	11.75" (29.84)	1.313" (3.02)	2.5" (6.35)	**073031212**
2 NPT	1.50"-1.70"	(3.81-4.32)	13.25" (33.65)	1.375" (3.49)	3.25" (8.25)	**073031213**
2½ NPT	1.70"-2.00"	(4.32-5.08)	13.5" (34.29)	1.5" (3.81)	3.625" (9.21)	**073031214**
2½ NPT	2.00"-2.45"	(5.08-6.22)	13.75" (34.92)	1.5" (3.81)	3.625" (9.21)	**073031215**

