Cable Splicing Grips

Double Weave, Galvanized Steel / Single Weave, Galvanized Steel

Splicing Grips

Splicing Grips are made of galvanized steel in double weave mesh construction. They are available in various lengths and sizes to suit most applications.

IMPORTANT

Read all breaking strength, safety and technical data relating to this product. Pages V-17 to V-26.



Double Weave Tube

Cable Diameter Range Inches (cm)	.37"-.49" (.94-1.24)	.50"-.61" (1.27-1.55)	.62"-.74" (1.57-1.88)	.75"-.99" (1.90-2.51)	1.00"-1.49" (2.54-3.78)
Approx. Breaking Strength Lbs. (N)	3,500 (15,568)	3,500 (15,568)	4,400 (19,571)	7,500 (33,360)	10,000 (44,480)
Mesh Length Inches (cm)	Catalog Number				
18" (45.72)	**013041330**	**01304064**	**01304009**	—	—
24" (60.96)	—	**01304011**	**01304013**	**01304010**	**01304015**
36" (91.44)	—	—	**013041234**	**01304054**	**01304055**
48" (121.92)	—	—	—	**01304017**	**01304029**
72" (182.88)	—	—	—	**01304037**	**013041333**

Junior Splicing Grips, Single Weave

Junior Splicing Grips are made of galvanized steel and are designed for use in very light duty and small splicing jobs.



Junior Tube

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs. (N)	Length @ Nom Diameter Inches (cm)	Catalog Number
.18"-.24" (.46-.61)	400 (1,779)	7" (17.78)	**01301008**
.25"-.36" (.63-.91)	400 (1,779)	8" (20.32)	**01301013**